

Designed and Manufactured in the UK Hawk Dome

Opening the World of Vision

Black Hawk Dome



External fully functional CCTV Dome with Dual IR Lamps

Dual IR Lamps	•	Dual 830nM wide angle IR Lamps that pan and tilt with the Black Hawk Dome give excellent night time pictures for up to 100 metres.	
IP67	•	Industry leading IP67 certification giving "Protection to withstand total immersion in water for 30 minutes".	
Multi Protocol integration	•	The Black Hawk Dome range comes with Multi Protocols as standard allowing complete integration with many leading DVR's, Matrices and IP Systems. Protocols built-in include 'TwistedPair' control from 360 Vision, Honeywell, Pelco P/D, Ultrak with 'in-coax' control from 360 Vision, BBV/Dennard plus Pelco Coaxitron	
On Screen Display (OSD)	•	The Black Hawk Dome OSD enables full access to all functions using either 360 Vision control systems or 3rd party protocols.	
Advanced Motion Control	•	360 Visions extensive Dome range, is driven by 360 Visions highly advanced motor control system, enabling extremely quiet, controllable and smooth with totally accurate operation and exact preset position selection.	
Economics	•	The Black Hawk Dome uses only the highest quality components for ultra reliability, combined with innovative design to support full remote diagnostics and reduce installation, operation and maintenance costs.	
Intelligent alarms	•	The intelligent alarm module allows up to 144 alarm inputs which can be remotely configured via the Vision matrix or any compatible third party system.	
Creative Privacy zones	►	32 privacy zones are available with simple joystick positioning and sizing.	
Colour/mono cameras	•	The Black Hawk Dome range includes 18x, 28x and 36x zoom with Autofocus featuring ExView camera technology which gives excellent low light performance with frame integration for usable images as low as 0.01lux. 360 Vision software enables the colour/mono switch over levels to be set for specific lighting conditions.	
Picture freeze	•	The on-screen visible image can be frozen whilst the Black Hawk Dome moves to preset positions allowing efficient DVR recording.	
Fast shutter option	•	For optimum performance with automatic number plate recognition systems.	

VISIONDOMES

Features

Colour / Mono
Imager
Zoom - optical
Zoom - digital total
Line resolution
Pixels
Horizontal view angle
Lens size
ExView technology
Min sensitivity - colour
Min sensitivity - colour int
Min sensitivity - mono int
Signal/noise ratio
Picture freeze
Picture flip

FEATURES

Video output
Signal
Focus/iris
Presets
Tours
Learned patrols
Dynamic privacy zones
Preset titling
Telemetry
Protocols - includes
Variable pan speed/coverage
Variable tilt speed
Tilt coverage
Auto homing
Col/mon changeover
Line lock
Operating temperature
Power
Recommended PSU
Mounting options
mounting options

Operational enhancements Certification







18x Col/Mono	28x Col/Mono	36x Col/Mono				
External	External	External				
YES	YES	YES				
1/4" ExView HAD	1/4" Super HAD	1/4" ExView HAD				
18x	28x	36x				
12x, 216x	12x, 336x	12x, 432x				
550	550	540				
752(H) x 582(V)	752(H) x 582(V)	752(H) x 582(V)				
2.8°(T) 48° (W)	2.1°(T) 55.8° (W)	2.7°(T) 57.8° (W)				
4.1 - 73.8 mm	3.5 - 98.0 mm	3.4 - 122.4 mm				
YES	NO	YES				
0.7 Lux	0.25 Lux (50 IRE)	1.4 Lux (50 IRE)				
0.04 Lux	0.016 Lux	0.1 Lux				
0.01 Lux	0.0015 Lux	0.01 Lux				
>50 dB	>50 dB	>50 dB				
YES	YES	YES				
YES	YES	YES				
All units have the following functions						
1 V p to p, 75Ω						
PAL or NTSC						
Auto / manual						
360						
4 (max 128 presets per tour)						
4 mimic tours - up to 30 minutes duration each						
Up to 32, 8 present on screen simultaneously, 4 levels of opacity						
	YES					
Coaxial or RS485 (auto select)						
RS 485: 360, Pelco P, Pelco D , Honeywell, Ultrak Coaxial-360, Pelco Coaxitron, BBV						
0.1 - 240°/sec, 360° continuous rotation, absolute positioning						
0.1 - 200°/sec, absolute positioning						
	90°					
Goes to preset, t	our or mimic tour after presc	ribed time (menu)				
3 levels - menu set up						
enable/disable						
-20 to 60°C						
VDE-PSU / PRED-PSU						
Wall,Corner, Swan Neck, Soffit, Pole						
Telemetry and power with onto isolation						


Telemetry and power with opto isolation Safety mark : CE approval; Ingress : IP67

360BHD130411v1

All trademarks are used courtesy of registered owners. Black Hawk Dome is a registered trademark of 360 Vision Technology Ltd. The manufacturer reserves the right to change specifications without notice.

360 Vision Black Hawk Domes are covered by a 3 year warranty (excluding IR Lamps) valid from delivery date. Warranty cover is based on return to 360 Vision UK Factory with a pre-issued RMA Number.





Black Hawk Dome options - available in Black or Cool Grey





Tel: +44 (0) 870 903 360 1, Fax: +44 (0) 870 903 360 2, info@360visiontechnology.com

360 Vision Technology Ltd, Unit 7 Seymour Court, Manor Park, Runcorn, Cheshire, WA7 1SY, UK