vision

Black Hawk Dome

.....with TWIN IR LAMPS

Designed and Manufactured

in the UK











External fully functional CCTV Dome with Dual IR Lamps

Dual IR Lamps
Dual 830nM wide angle IR Lamps that pan and tilt with the Black Hawk Dome give excellent night time pictures for up to 70 metres (40m and 70m options available).

IP67 ▶ Industry leading IP67 certification giving "Protection to withstand total immersion in water for 30 minutes".

Multi Protocol integration > The Black Hawk Dome range comes with Multi Protocols as standard allowing complete integration with many leading DVR's, Matrices and IP Systems. Protocols built-in include 'TwistedPair' control from 360 Vision, Honeywell, DM, Pelco P/D, Ultrak with 'in-coax' control from 360 Vision plus Pelco Coaxitron

On Screen Display (OSD) > The Black Hawk Dome OSD enables full access to all functions using either 360 Vision control systems or 3rd party protocols.

Advanced Motion Control >

360 Visions extensive Dome range, is driven by 360 Visions highly advanced motor control system, enabling extremely quiet, controllable and smooth with totally accurate operation and exact preset position selection.

Economics >

The Black Hawk Dome uses only the highest quality components for ultra reliability, combined with innovative design to support full remote diagnostics and reduce installation, operation and maintenance costs.

Intelligent alarms

The intelligent alarm module allows up to 144 alarm inputs which can be remotely configured via the Vision matrix or any compatible third party system.

Creative Privacy zones >

32 privacy zones are available with simple joystick positioning and sizing.

Colour/mono cameras

The Black Hawk Dome range includes 18x, 26x and 36x zoom with Autofocus featuring ExView camera technology which gives excellent low light performance with frame integration for usable images as low as 0.01lux. 360 Vision software enables the colour/mono switch over levels to be set for specific lighting conditions.

Picture freeze >

The on-screen visible image can be frozen whilst the Black Hawk Dome moves to preset positions allowing efficient DVR recording.

Fast shutter option

For optimum performance with automatic number plate recognition systems.

Black Hawk Dome Features Colour / Mono **Imager** Zoom - optical Zoom - digital total **Line resolution Pixels** Horizontal view angle Lens size ExView technology Min sensitivity - colour Min sensitivity - colour int Min sensitivity - mono int Signal/noise ratio

Picture freeze Picture flip	
FEATURES	

Video output Signal Focus/iris **Presets** Tours Learned patrols Dynamic privacy zones **Preset titling Telemetry** Protocols - includes Variable pan speed/coverage Variable tilt speed Tilt coverage **Auto homing** Col/mon changeover Line lock Operating temperature Power **Recommended PSU**

Mounting options

Certification

Operational enhancements





n	
Swan Neck Bracket	

Pole Mounting Clamp

available in Black o	r Cool
Corner Mou	nt Bracket

18x Col/Mono	26x Col/Mono	36x Col/Mono
External	External	External
YES	YES	YES
1/4" ExView HAD	1/4" ExView HAD	1/4" ExView HAD
18x	26x	36x
12x, 216x	12x, 312x	12x, 432x
520	520	520
752(H) x 582(V)	752(H) x 582(V)	752(H) x 582(V)
2.8°(T) 48° (W)	2.2°(T) 54.2° (W)	2.7°(T) 57.8° (W)
4.1 - 73.8 mm	3.5 - 91.0 mm	3.4 - 122.4 mm
YES	YES	YES
0.7 Lux	1 Lux (50 IRE)	1.4 Lux (50 IRE)
0.05 Lux	0.07 Lux	0.1 Lux
0.01 Lux	0.01 Lux	0.01 Lux
>50 dB	>50 dB	>50 dB
YES	YES	YES
YES	YES	YES

TLO	1L5	TEO		
All units have the following functions				
1 V p to p, 75Ω				
PAL or NTSC				
Auto / manual				
360				
4 (max 128 presets per tour)				
4 mimic tours - up to 30 minutes duration each				
Up to 32, 8 present on screen simultaneously, 4 levels of opacity				
YES				
Coaxial or RS485 (auto select)				
RS 485: Pelco P, Pelco	D D ,DM, BBV, Honeywell Coaxid	al-360, Pelco Coaxitron		
0.1 - 240°/sec,	360° continuous rotation, abs	solute positioning		
0.1	I - 200°/sec, absolute position	ning		
	90°			
Goes to preset, tour or mimic tour after prescribed time (menu)				
3 levels - menu set up				
enable/disable				
-40 to 50°C with optional Dual Heater				
24Vac				
VDE-PSU / PRED-PSU				
Wall, Corner, Swan Neck, Soffit, Pole				
Telemetry and power with opto isolation				
Safety mark : CE approval; Ingress : IP67				

All trademarks are used courtesy of registered owners. All trademarks are used countesy of registered owners.

Black Hawk Dome is a registered trademark of 360 Vision Technology Ltd.

The manufacturer reserves the right to change specifications without notice.

360 Vision Black Hawk Domes are covered by a 3 year warranty (excluding IR Lamps) valid from delivery date. Warranty cover is based on return to 360 Vision UK Factory with a pre-issued RMA Number.





Black Hawk Dome options -I Grey



Tel: +44 (0) 870 903 360 1, Fax: +44 (0) 870 903 360 2, info@360visiontechnology.com