CCTV Equipment

VIDEO LEVEL DETECTOR

TYPE BH125B DATA SHEET

- An essential aid for the installer
- Designed for twisted pair cable
- Portable hand held unit
- Can be operated from internal battery or mains supply



APPLICATION

The BH125B Video Level Indicator will aid the installer in checking and adjusting a range of CCTV equipment. The unit is designed foe use with twisted pair cable.

The unit is connected to the output of the equipment under test. The video level detected is then clearly displayed on the LED array in the front panel. If no video is detected then a red lamp flashes.

The BH125B can be operated from its internal battery or from a 12V DC regulated supply that also charges the battery when connected. The 12V power supply is included with the unit.

Addlestone Electronics Ltd.

DESIGNED AND MANUFACTURED IN UK

TWISTED PAIR INPUT Miniature PCB socket for 150 ohm input.

CONNECTION

VIDEO LEVEL DISPLAY Orange LED array on front panel

NO VIDEO WARNING Red lamp in centre of front panel.

INTERNAL CALIBRATION

CONTROL

Factory set.

POWER REQUIREMENTS +12 V dc regulated supply.

BATTERY LIFE Approx. 2 hours of average use.

BATTERY RECHARGING

PERIOD

Approx. 12 hours for completely flat battery.

BATTERY ON/OFF INDICATOR Green lamp in left hand side panel.

On left hand side panel of unit. **BATTERY ON/OFF SWITCH**

POWER SUPPLY DETAILS INPUT: 230V ac @ 50 Hz 12 Watts

OUTPUT: +12V dc supply (max. of 300 mA /3.6 VA)

OPERATING TEMP.

RANGE

-10°C to +40°C.

CONSTRUCTION OF

BH125B CASING

Casing constructed of moulded FR- ABS plastic.


WEIGHT OF BH125B UNIT


225 grams (excluding power supply).

DIMENSIONS OF UNIT

Height 169mm Depth 35mm

Width 86mm (excluding switch)







Addlestone Electronics Ltd

Springfields, Church Lane, Bisley, Woking, Surrey. GU24 9EA

Telephone: (01483) 480969 Fax: (01483) 797268 E-mail: sales@addlestone-electronics.co.uk Web Site: www.addlestone-electronics.co.uk