VIDEO LEVEL DETECTOR

TYPE BH125U DATA SHEET

- An essential aid for the installer
- Designed for coaxial cables
- Portable hand held unit
- Can be operated from internal battery or mains supply



APPLICATION

The BH125U Video Level Indicator will aid the installer in checking and adjusting a range of CCTV equipment such as Launch Amplifiers, Distribution Amplifiers and Video Line Correctors. The BH125U is designed for use with coaxial cables.

The unit is connected to the output of the equipment under test. The video level detected is then clearly displayed. If no video signal is detected then a red lamp flashes on the front panel.

The BH125U can be operated from its internal battery or from a 12V DC regulated power supply that also charges the unit when connected. The 12V power supply is included with the unit.

Addlestone Electronics Ltd
DESIGNED AND MANUFACTURED IN UK

COAXIAL INPUT CONNECTION

75 ohm BNC socket.

VIDEO LEVEL DISPLAY

Orange light emitting diode array on front panel.

NO VIDEO WARNING

Red lamp in centre of front panel.

INTERNAL CALIBRATION

CONTROL

Factory set.

POWER REQUIREMENTS

+12V dc regulated supply.

BATTERY LIFE

Approx. 2 hours of average use.

BATTERY RECHARGING

PERIOD

Approx. 12 hours for completely flat battery.

BATTERY ON/OFF INDICATOR

Green lamp in left hand side panel of unit.

BATTERY ON/OFF SWITCH

On left hand side panel of unit.

POWER SUPPLY DETAILS

INPUT: 230V ac @ 50 Hz 12 Watts

OUTPUT: +12V dc supply (max. of 300 mA /3.6 VA)

OPERATING TEMPERATURE

RANGE

-10°C to +40°C.

CONSTRUCTION OF

BH125U CASING

Casing constructed of moulded FR- ABS plastic.

WEIGHT OF BH125U UNIT


225 grams (excluding power supply).


DIMENSIONS OF UNIT

Height 169mm

Depth 35mm

Width 86mm (excluding switch)







Springfields, Church Lane, Bisley, Woking, Surrey. GU24 9EA

Telephone: (01483) 480969 Fax: (01483) 797268 E-mail: sales@addlestone-electronics.co.uk Web Site: www.addlestone-electronics.co.uk

