

Overview

This Altronix Outdoor Power Supply provide a 24VAC or 28VAC distributed via one or two output(s) for powering CCTV Cameras, heaters and other video accessories.



Specifications

Input:

• Input: 115VAC, 50/60Hz, 1.2 amp or 230VAC, 50/60Hz, 0.7 amp.

Output:

- Output options:
 - a. 24VAC @ 4 amp max.
 - b. 28VAC @ 3.5 amp max.
 - c. Both 24VAC and 28VAC not to exceed 3.5 amp max.
- Output fuses rated @ 5A 250V.

Electrical:

- Operating Ambient Temperature: -20° C to 50° C.
- Total system power consumption: 100 W.
- 38 BTU/Hr.:
- System AC input VA requirement: 100VA.

Mechanical:

- NEMA 4/4X, IP66-11 Rated enclosure for outdoor use.
- Lightweight molded fiberglass reinforced polyester enclosure is corrosion resistant and does not contain halogens.
- Lockable stainless steel latches.
- Integral flanges simplify wall or pole mounting.
- Enclosure Dimensions (H x W x D approx.): 13.31" (338.074mm) x 11.31" (287.274mm) x 5.59" (141.986mm)
- Product weight (approx.): 11.45 lbs. (5.19 kg.).
- Shipping weight (approx.): 12.75 lbs. (5.78 kg.).

Features:

- Individual power output LEDs.
- Spare fuses included.

Agency Approvals



Enclosure Dimensions (H x W x D): 13.31" (338.074mm) x 11.31" (287.274mm) x 5.59" (141.986mm)

