

DATASHEET | VIDEO | EN-7904 FOUR CHANNEL VIDEO ENCODER





VISUALIZER™ EN-7904 FOUR CHANNEL VIDEO ENCODER

An encoder provides an ideal way to upgrade existing analog video cameras to offer all the advantages available from digital video. The Visualizer EN-7904 network video encoder provides 4 input channels and uses the latest H.264 compression, which dramatically reduces file sizes by up to 80% for easy storage and network transmission.

Efficient operation allows ease of monitoring, management and maintenance, and reduces the demand on time and resources. Cost savings are also introduced as multiple or complex sites can be monitored from one central location. Using the Visualizer EN-7904 network video encoder in combination with Symmetry Video Management Software delivers a complete high performance, seamless video solution for use with low cost analog cameras.

The EN-7904 includes, at no extra cost, "Intelligent Motion Detection", which uses a unique tracking engine to perform intelligent analysis of motion for intrusion and tamper detection. These features include:

- Intruder and Perimeter Detection tracks up to 100 moving and stationary targets to generate real time alerts on objects present in up to 40 overlapping detection zones
- Camera Tamper Detection generates a tamper alarm if the camera is covered or if the camera is moved or otherwise adjusted to affect the camera view.

Optional Video Content Analytics (VCA) extend the capabilities of the Intelligent Motion Detection to include additional options for entry, exit, appear, disappear, dwell, direction, abandoned, removed objects and counting linked to the detection rule. These enhanced VCA features allow intelligent analysis of motion in a variety of application areas.

To make full use of the features available in these encoders requires Symmetry Security Management Software v6.2 SP4a or later, with Visualizer EN-7900 Series Video Plug-in.

KEY FEATURES

- Video encoder for monitoring up to 4 analog cameras
- Robust compact metal enclosure
- H.264 encoding
- 25/30fps @ D1 on all channels
- Intelligent Motion Detection per input channel
- Advanced Video Analytics per input channel (optional)
- Deinterlacing on DSP
- Connects directly to LAN / WAN 10/100 Base-T
- Three Year Warranty
- Integrates with Symmetry Security Management Software
- RS232, RS485
- 4 digital inputs





SPECIFICATIONS	EN-7904 NETWORK H.264 ENCODERS
TV System	Auto detection of NTSC and PAL
Resolution	DI, 4CIF, VGA, CIF, QVGA, QCIF
Functions	TCP/IP, UDP/IP, HTTP, RTSP, RTCP, RTP/UDP, RTP/TCP, SNTP, mDNS, UPnP, SMTP, SOCK, IGMP, DHCP, DDNS, SSL v2/v3, IEEE 802.IX, SSH, FTP
Power Source	12 VDC, Power block included
Power Consumption	I,100 mA @ 12V
Operating Temperature	-20°C to 60°C (4°F – 140°F) Up to 85% RH (non-condensing)
Color	Black
Dimensions	W: 137mm (5.4in) H: 38mm (1.5in) D: 189mm (7.4in)
Compression	H.264
Frame Rate	25/30fps @ DI
Intelligent Motion Detection	Intrusion detection, tamper detection for obscuration, defocus and movement
Video Content Analytics (optional)	Direction, stopping, loitering, entering, exiting, appear, disappear, dwell, abandoned and removed objects, counting linked to detection rule (EN-7904-VCA)
PURCHASING INFORMATION	DESCRIPTION
EN-7904-A	4 channel encoder with Intelligent Motion Detection per channel
VCA-LIC-001-A	Single Channel Video Content Analytic License
VCA-LIC-004-A	Four Channel Video Content Analytic License



AMAG Technology

sales@amag.com www.amag.com