



## ADTTE TOUCH TRACKER® MATRIX KEYBOARD



### FEATURES

- Attractive ergonomic design
- Backlit LCD display
- Camera, monitor and satellite site selection
- Variable-speed Tracker Ball control of pan/tilt and dome
- Lens control (zoom, focus, iris)
- Supports dome “flip” feature
- Preset, pattern and auxiliary control
- Tour control
- Salvo control
- Alarm control
- Supports multiple languages (English, French, Spanish, German, Italian, Portuguese)
- Built-in self-test to verify hardware and software operation

The ADTTE Matrix Switcher/Controller Keyboard is compact, ergonomically-designed and compatible with MegaPower™ Series Matrix Switcher/Controller Systems. This keyboard provides you with easy access to a complete selection of video switching options – from basic camera and monitor selection to the most advanced automatic control.

The tracker ball provides control of fixed and variable-speed pan/tilts and domes. Buttons enable you to control lens zoom, focus, and iris functions. The keypad contains buttons that allow you to assign any camera to any monitor, and access special features such as salvos, tours, and alarms.

The LCD displays the currently selected camera, monitor, and site. It also enables you to see the numbers you enter from the keypad as you enter them, and it displays system prompts and messages.

# AMERICAN DYNAMICS ADTTE TOUCH TRACKER® MATRIX KEYBOARD

## SPECIFICATIONS

### Model Number

ADTTE ..... Matrix Keyboard, 120 or 230 VAC

Note: The ADTTE is suitable for use worldwide. Proper low-voltage transformer, with main power cord, is supplied with the unit. Specify country of installation and 120 or 230 VAC at time of order.

### Electrical

Input Voltage ..... 16 to 32 VAC, 50/60 Hz

Power ..... 10.8 watts

### Mechanical

Dimensions (H x W x D) ..... 130 x 194 x 260 mm  
(5.12 x 7.63 x 10.24 in)

Weight ..... 1 kg (2.2 lbs)

Color ..... Black shell with gray appliqué

### Environmental

Operating Temperature ..... 0° to 50° C (32° to 122° F)

Humidity ..... 5-95% RH (non-condensing)

Storage Temperature ..... -20° to 65° C (-4° to 149° F)

### Regulatory

Emissions ..... FCC: 47 CFR Part 15,  
Subpart B, Class A  
CE: EN55022 Class B  
CE: EN6100-3-2  
CE: EN6100-3-3  
AS/NZS 3548, Class A  
CISPR22  
ICES-003

Immunity ..... CE: EN50130-4

Safety ..... UL: UL1950  
cUL: CSA 22.2 No. 950  
IEC950  
CE: EN60950



**ADTTE Touch Tracker Matrix Keyboard Layout**

(EIM Module and Transformer are supplied with the ADTTE)