

Model Numbers:

AV20185DN	180° Panoramic Day/Night
AV20365DN	360° Panoramic Day/Night
AV20185DN-HB	180° Panoramic Day/Night with Heater & Blower
AV20365DN-HB	360° Panoramic Day/Night with Heater & Blower

Imaging

- Four 5 megapixel CMOS image sensors
- 2592(H) x 1944(V) pixel array each sensor
- 1/2.5" optical format
- 2.2 μ m pixel pitch
- Bayer mosaic RGB filter
- Minimum illumination of:
 - Color(non-binned): 0.3 Lux @ F1.8
 - Color(binned): 0.15 Lux @ F1.8
 - Day/Night: 0 Lux, IR sensitive
- Dynamic range 70.1 dB
- Maximum SNR 44.1 dB

Full Field of View (FOV) Resolution

- 10368(H) x 1944(V) = 2592(H) x 1944 (V) x 4
20 megapixel total
- 5184(H) x 972(V) = 1296(H) x 972(V) x 4
5 megapixel total

Data Transmission

Video frame rate up to:

- 2.8 fps @ 10368x1944
- 3.4 fps @ 10240x1600
- 11.5 fps @ 2952x1944
- 13.8 fps @ 2560x1600

Compression type:

- H.264 (MPEG4, Part 10)
- Motion JPEG
- 21 levels of quality

Support Protocols:

TFTP, HTTP, RTSP, RTP over TCP, RTP over UDP
100Base-T Ethernet Network Interface

Data rate:

- bit rate control from 100Kbps to 10Mbps
- unthrottled data rate up to 50Mbps

Multi-streaming: 8 non-identical streams

Programmability

- +/- 5° Electrical Vertical Alignment to adjust sensor position (AV2105DN)
- Privacy mask
- Auto Exposure (AE) and Gain Control (AGC) >120dB
- On-camera real-time motion detection with 1024 detection zones
- Auto backlight compensation
- Auto multi-matrix white balance
- 50/60Hz selectable flicker control
- Electronic pan, tilt, zoom (PTZ)
- Electronic image flip - 180 degree rotation
- Resolution windowing down to 1x1 pixel for JPEG and 2x2 pixels for H.264
- Programmable shutter speed to help control motion blur
- MoonLight™ mode - extended exposure and proprietary noise cancellation
- Programmable resolution, brightness, saturation, gamma, sharpness, tint
- Picture-in-Picture: simultaneous delivery of full field of view and zoomed images
- Bandwidth & storage savings by running at 1/4 resolution

Electrical

- General purpose opto-coupled input and output
- Power over Ethernet (PoE): PoE 802.3af for camera
- Auxiliary power 12-48V DC, 24V AC
- Power consumption: 9 watts maximum

Mechanical

- +/- 10° tilt adjust to locate sensor angle (AV20365DN)
- Easily adjustable 2-axis camera gimbal with 360° pan and 90° tilt
- Hard ceiling mount and surface mount embedded
- Die-cast aluminum chassis with 5.5" vandal resistant polycarbonate dome bubble
- Conduit it 3/4" NPT standard
- Total Unit dimensions:
 - \varnothing 6.9 x 6.55 in (H), bubble only: \varnothing 5.5 x 3.4 in (H)
 - \varnothing 175 x 166 mm (H), bubble only: \varnothing 140 x 87 mm (H)
 - 3.81 lbs (1.75 kg)

Heater & Blower Electrical

- Voltage Input: 12V to 20V DC/24VAC (separate power required)
- Power Output: 11W Max (DC12V); 13W Max (AC24V)
- Heater Switch: On: 17°C (62.6 °F), Of: 30 °C (86 °F)
- Blower Switch: On: 10°C (50°F), Of: 15 °C (59 °F)
- Blower Switch: On: 50°C (122 °F), Of: 45 °C (113°F)

Regulatory Approvals

- FCC, CE, RoHS, cULus

Environmental

- IP66 weatherproofing standard
- Operating temperature:
 - No Heater: 0°C (32 °F) to +55°C (131 °F)
 - With Heater: -30°C (-22 °F) to +55°C (131 °F)
- Storage temperature: -40 °C (-40 °F) to 60 °C (140 °F)
- Humidity 0% to 90% (non condensing)

Accessories:

- SV-WMT - Indoor/Outdoor Wall Mount
- SV-CMT - Indoor/Outdoor Ceiling Mount
- SV-FMA - Indoor/Outdoor Flush Mount Adapter
- MD-PMA - Indoor/Outdoor Pole Mount Adapter
- MD-CRMA - Indoor/Outdoor Corner Mount Adapter
- MV-EBA - Indoor/Outdoor Electrical Box Adapter

