

## **COVERT CAMERA**

## **MONOCHROME**

## **DD 400/MSAW**

 DD 400 detector case containing monochrome camera with standard lens, audio and operational PIR

One of a range of PIR cameras designed for the professional security installer using the latest miniature camera and passive infrared technology.

- An ideal camera for detecting rather than deterring crime
- Excellent picture quality
- Discreet, stylish case designed to blend inconspicuously into any commercial environment
- Ideal for use where DD 400 detectors are already installed
- Comes with pre-focused (1m ∞) factory-fitted lens
- Ideal for the video verification of alarms
- Simple and speedy to install
- Standard rather than pinhole lens for improved performance in low light conditions
- Can be used to trigger a VCR or video switcher to which the camera is connected
- Contains anti-tamper switch and 'normally-closed' alarm switch
- Comes with free audio capability
- Comes with lint-free cleaning cloth to remove grease and dirt from case and lens
- No microwave element as in DD 400 detector.



 $\leq$ 

1/3" CCD



380 TV lines



0.3 lux sensitivitySupply voltage: 12 Vdc



Audio output: 1V p-p

Lens option		
Lens	<b>Product Code</b>	
4.0mm	DD 400/MSAW	

## See Also:



EV 400/CSA EV 400 detector case containing colour camera with standard lens and audio



EV 400/CPA EV 400 detector case containing colour camera with pinhole lens and audio



EV 500/MSAW Monochrome pinhole camera inside working EV 500 PIR

	SPECIFICATION	MOD-308/A camera module
	Image sensor	1/3" CCD sensor, 512 (H) x 582 (V) pixels
	Horizontal resolution	380 TV lines or greater
	Lens options	SEE TABLE
Ю	Electronic shutter	Automatic linear shutter
ND	Sensitivity	0.3 lux
	Video output	CCIR, 1Vp-p, 75 Ohms
	Supply voltage	12 Vdc <u>+</u> 10%
	Working temperature	-18°C to +60°C
0	Microphone	Omni-directional electret
AUDIO	Audio output	1Vp-p, 600 Ohms
A	Audio bandwidth	100Hz - 10KHz, +/- 3dB