

**COVERT CAMERA**  
**MONOCHROME**

## EV 400/MSA

- EV 400 detector case containing monochrome camera with standard lens and audio

One of a range of PIR cameras designed for the professional security installer using the latest miniature camera technology.

- An ideal camera for detecting rather than deterring crime
- Excellent picture quality
- Discreet, stylish case designed to blend inconspicuously into any commercial environment
- Ideal for use where EV 400 detectors are already installed
- Comes with pre-focused (1m - ∞) factory-fitted lens
- Ideal for the video verification of alarms
- Simple and speedy to install
- Comes with versatile wall or ceiling mount bracket for exact camera positioning
- Standard lens views through clear viewing window for improved performance in low light conditions
- Scratch-resistant camera viewing window for easy maintenance
- Comes with free audio capability
- Comes with lint-free cleaning cloth to remove grease and dirt from case and lens



- 1/3" CCD
- 380 TV lines
- 0.3 lux sensitivity
- Supply voltage: 12 Vdc
- Audio output: 1V p-p

### Lens options

Lens	Product Code
<b>4.0mm</b>	<b>EV 400/MSA</b>
2.5mm	EV 400/MSA/2.5
6.0mm	EV 400/MSA/6.0
8.0mm	EV 400/MSA/8.0
12.0mm	EV 400/MSA/12.0

All lens options are the same price

### See Also:



EV 400/CSA  
Colour version



EV 400/MPA  
Monochrome  
pinhole version



EV 500/MPAW  
Monochrome  
pinhole camera  
inside working EV  
500 PIR

### SPECIFICATION

	MOD-308/A camera module
Image sensor	1/3" CCD sensor, 512 (H) x 582 (V) pixels
Horizontal resolution	380 TV lines or greater
Lens options	SEE TABLE
Electronic shutter	Automatic linear shutter
Sensitivity	0.3 lux
Video output	CCIR, 1Vp-p, 75 Ohms
Supply voltage	12 Vdc ± 10%
Working temperature	-18°C to +60°C

### VIDEO

### AUDIO

Microphone	Omni-directional electret
Audio output	1Vp-p, 600 Ohms
Audio bandwidth	100Hz - 10KHz, +/- 3dB