



Accu-Time Systems, Inc.

Series 5000

The Accu-Time Series 5000 is a true "C" download programmable, intelligent shop floor data collection terminal. Offerings of the Series 5000 include a large, capacitor backed memory base of 128K and an optional 64K of Flash memory for file validation, local editing and scheduling functions. This ideal shop floor data collection terminal has open ACCU-TECTURE[®] modular connectivity, enhanced I/O options for device integration, and feature-rich industrial packaging. The Series 5000 is a vital component to any management information system.

- ▶ Single or multi-clock environments
- ▶ 128K Byte memory base (capacitor backed)
- ▶ EIA Standard RS232 or RS485 compatible
- ▶ Integrated and/or external bar code reader
- ▶ Integrated magnetic slot readers
- ▶ Digital bar code wand port
- ▶ TCP/IP Ethernet 10-base-T compatible
- ▶ Relay and printer interface modules
- ▶ Low voltage power source (local or remote)
- ▶ Die cast aluminum housing w/lockable base



Accu-Time Systems, Inc.

t: 860.870.5000

f: 860.872.1511

www.accu-time.com

ACCU-TIME®

Series 5000

Specifications

DISPLAY	2 or 4 line x 40 character super-twist LCD (backlit option available)
CLOCK	12 or 24 hour format — USA or International (quartz precision) Time stamp of data transactions
INDICATORS	Yellow LED low power indicator Red and green programmable LED indicators Four diagnostic LEDs for Ethernet: Yellow = busy; Green = linked Yellow = receive; Red = transmit
KEYPAD	Software defined function keys Large 20 key tactile 4x5 matrix Custom user-defined keypad legends
SPEAKER	Dual tone audible annunciator
MEMORY	128K Byte of capacitor backed memory (i.e. 600-employee base — program dependent) Expandable to 768K Byte (i.e. over 2000 employees program dependent) 64K Flash memory (optional)
PROGRAMMING	ATS DATA TRAKER™ modules, C programming language or third party custom application packages
SELF-TEST	ACCURATE™ on-board terminal set-up and full-feature diagnostics
INTERFACE	TCP/IP Ethernet 10-base-T (802.3) EIA Standard RS232 or RS485 (2 or 4 wire) Standard AT Command Set for internal 9600/19.2 Baud modem DI/DO or serial interface printer port Digital bar code wand input port
ENCLOSURE	Die cast aluminum housing with steel key-lockable base assembly
POWER	+10 to +17 VDC (+12 VDC @ 400 milliamps Nominal) Local, remote or centrally powered Non-interruptible power source with charger (optional)
ENVIRONMENT	32° to 110°F (0° to 43°C)
CERTIFICATION	CE Mark Certified (CE, RE, ESD, RS and CS), FCC part 15
PHYSICAL	7.25" L x 11.5" W x 3.4" H Weight: 5.3 lbs. (18.42 cm L x 29.21 cm W x 8.64 cm H Weight: 2.4 kg)
ACCESSORIES	Integrated or external optical bar code slot reader Integrated magnetic slot readers Digital bar code wands, RF ID readers Solid state or dry contact relay modules Serial interface printer port



Accu-Time Systems, Inc.
One Accu-Time Plaza
420 Somers Road
Ellington, CT 06029
1-800-355-4648
Tel: (860) 870-5000
Fax: (860) 872-1511
E-mail: sales@accu-time.com

Accu-Tech Systems LLC
26 Orion Suite
Enterprise Way
Newport, U.K. NP20 2AQ
Tel: +44-1633-84-0000
Fax: +44-1633-84-1000
www.accu-time.com

Accu-Time, whose policy is one of continuous improvement, reserves the right to change specifications without notice.