FA4516

Advanced Technology Video, Inc.



- Display speed of up to 480ips NTSC (400 PAL) on a single, quad, 3+4,3X3,2+8, and 4X4 screen
- Recording speed of up to 120 images per second (100 PAL)
- Monitor live video images on the DVR through internet web browser

Ç

Optional ATM/POS interface

Series

X K

- 250 GB hard drive storage, expandable up to 4 hard drives
- Audio recording and playback
- · Pentaplex operation, Simultaneous recording, multiscreen viewing, playback, remote monitoring and archiving
- Backup to external SCSI hard disk drives, USB hard disk drive, Jaz drive
- Synchronizes to time server
- Remote monitoring, playback and configuration through LAN, PTSN, and ISDN

FA4516 SPECIFICATIONS

VIDEO

Signal Format Video Input Monitor Outputs NTSC or PAL (programmable) Composite: 16 inputs, 1 Vp-p, auto-terminating, 75 Ohms Composite: One, 1 Vp-p, auto-terminating, 75 Ohms VGA: One 640 x 480, 640 x 240, 320 x 240, 160 x 120

 Becording Resolution
 640 x 480, 640 x 240, 320 x 240, 160 x 120

 Display/Record Speed (IPS)
 Max. 480ips / 120 ips
 (100ips / 400 ips for PAL)

Composite: 16 BNC

Composite: 16 BNC

1 Line in

1 Line out

RJ-45

DB9 (P)

Terminal Block

RJ-11 or RS-232

Standard 68 (P) SCSI II

EIDE hard disk drives

Internal: floppy drive,

19.1" x 7.0" x 15.8"

23.6" x 11.7" x 21.7"

24.5lb (11.1Kg)

33.1lb (15.0kg)

(485mm x 177mx v 400mm)

(600mm x 296mm x 550mm)

External: SCSI hard disk drive, USB hard disk drives, Zip or Jaz drive

USB Connector

25 (P) D-Sub

Composite: 1 BNC, 1 VGA

INPUTS & OUTPUTS

Alarm Input Alarm Output Audio Input Audio Output 16 switch closure or TTL open-collector 1 relay, 16 TTL 1 line input 1 line output

CONNECTORS

Video Input Video Loop Output Monitor Output Audio In Audio Out Alarms Ethernet port Modem Port RS232 Serial Port USB Port Parallel Port SCSI

STORAGE

Primary Storage Secondary Storage

GENERAL

Dimensions (W x H x D)

Unit Weight Shipping Dimensions

Shipping Weight Power

MISCELLANEOUS

Approvals Compatible Options FCC, CE, UL IDE extension card*1**, SCSI**, Secondary storage devices

100 to 220 VAC, 50/60hHz

FALCON XR SERIES POS

FA-POS1	
FA-POS4	
FA-POS8	
FA-POS16	


XR series 1 input POS license (FA-4516 only) XR series 4 input POS license (FA-4516 only) XR series 8 input POS license (FA-4516 only) XR series 16 input POS license (FA-4516 only)


*Four additional hard disk devices may be installed.

** Do not use both IDE extension card and SCSI card at the same time


Specifications subject to change without notice.

DIMENSIONS





APPLICATION DIAGRAM





Advanced Technology Video, Inc. 10940 NE 33rd Place, Suite 101, Bellevue, WA 98004 888/228-7644 Fax 425/284-2952 www.atvideo.com