Advanced Technology Video, Inc.



16 Channel Digital Video Recorder

- Multiple recording modes: time-lapse, event-driven and pre-event recording
- Dual scheduling
- Various camera displays: single-screen, full screen, quad, 3+4, 3x3, 2+8 and 4x4
- Provides auto/manual backup to DVD-RAM, CD-RW and USB hard disk drive
- PTZ Control: Supports various receivers and dome cameras
- Monitors live video images on the DVR through internet web browser any time from virtually anywhere using the remote web monitoring program
- Time Synchronization: Synchronizes the time between the DVR and any time server
- Audio recording and playback
- Programmable Video Motion Detection
- Remote monitoring, Playback and control through LAN, PSTN and ISDN
- Encrypted
- Password-Protected Access
- Supports most Windows compatible printers
- Archive any video clip as an ".exe" file with self player software
- Programmable Alarm Priority
- Up to 1 minute of pre-event recording
- . Email notification: Sends an email when events occur
- Pentaplex operation, simultaneous recording, multiscreen viewing, playback, remote monitoring and archiving
- Records up to 120 ips for NTSC and 100 for PAL
- Watchdog software for increased stability

PC16-120 SPECIFICATIONS

VIDEO

Signal Format NTSC or PAL Programmable

Video Input Composite: 16 inputs, 1 Vp-p, selectable

75 Ohms or High-z termination

Monitor Output Composite: One, 1Vp-p, 75 Ohms

VGA: One

Recording Resolution 640x480, 640x240, 320x240,

160x120

Display/Record speed Max. 120ips/120ips (100ips/100ips

for PAL)

INPUTS & OUTPUTS

Alarm Input 16 switch closure or TTL open-collector

Alarm Output 1 relay

Audio Input One, "line in" or "mic" programmable

Audio Output One, "line"

CONNECTORS

Video Input Composite: 16 BNC
Monitor Output Composite: 1 BNC : 1 VGA
Audio In Line in or microphone in

 Audio Out
 Line out

 Alarms
 Terminal Block

 Ethernet Port
 RJ-45

 RS232 Serial Port
 DB9 (P)

USB Port 4 USB connectors **Parallel Port** 25 (P) D-Sub

STORAGE

Primary Storage EIDE hard disk drives
Secondary Storage Internal: DVD-RAM, Jaz drive

Backup Storage CD-RW

GENERAL

Dimensions (W x H x D) 16.7" x 6.3" x 17.7"

(425mm x 160mm x 450mm)

Shipping Dimensions 21.3" x 12.6" x 21.7"

(540mm x 320mm x 550mm)

 Unit Weight
 25.8lbs. (11.7kg)

 Shipping Weight
 35.5lbs. (16.1kg)

 Power
 100 - 127V ~ 6A,

 200-240V ~ 3A, 60/50Hz

MISCELLANEOUS

Operating System Windows Home Edition

Hardware Components Intel PIV Celeron, 128 MB PC2100 DDR SDRAM,

LG CDRW Drive, 10/100 Intel LAN adapter

onboard

Specifications subject to change without notice.

APPLICATION DRAWING

