

Seikou Optical Ltd.

| Model No. | | | | TVSG5533 |
|--------------------------------|-------------------------|-----------|---------|--------------------------------|
| Image Format Cover | | | | 1/3" ~ 1/4" |
| Focal Length | | | | 5.5 ~ 33mm |
| Maximum Aperture Ratio | | | | 1:1.6 |
| Zoom Ratio | | | | 6X |
| | Control Method | | | Video Drive |
| Iris | Iris Range | | | F1.6 ~ 360 |
| | Speed | | | Approx.1.5sec |
| | Input Voltage & Current | | | DC8 ~ 16V Max.35mA |
| | Sensitivity Adjustment | | | 0.5 ~ 1.0Vp-p |
| Focus | Control Method | | | Manual |
| Zoom | Control Method | | | Manual |
| | | 1/4 inch | Wide | 46.8°X37.2°X27.7° |
| Angle F of View (DXHX) | ield | | Tele | 8.1°X6.5°X4.8° |
| | Λ | 1/0 in ab | Wide | 63.9°X50.1°X37.2° |
| | /) | 1/3 inch | Tele | 11.0°X8.7°X6.5° |
| Minimum Object Distance | | | | 0.3m |
| Back Focal Length | | | | 10.3 ~ 13.0mm |
| Effective Diameter Front | | Front | ø34.0mm | |
| Rear | | | Rear | ø7.8mm |
| Filter Screw Size | | | | M40.5 P=0.5 |
| Mount / Flange Back | | | | CS/12.5mm |
| Mechanical Dimension (DX(H)XL) | | | | ø42mmX54.3mmX54.5mm |
| Total Weight | | | | 146.0g |
| Application Temperature Range | | | | -10°C ~ +50°C (+14°F ~ +122°F) |
| Remarks | | | | |

