

# AXIS Companion Bullet mini LE

## Outdoor full HD IR network camera

AXIS Companion Bullet mini LE is a small and discreet, outdoor-ready day/night camera with built-in IR illumination for surveillance in total darkness. The bullet-style camera has a compact, flat-faced design that suppresses reflections and WDR technology delivering high image quality even in scenes with complex light conditions. The camera features Power over Ethernet (PoE) that allows one cable to provide both network connectivity and electrical power. AXIS Companion Bullet mini LE is supported only by AXIS Companion video management software and mobile app, and requires an AXIS Companion Recorder for system completion.

- > **High video quality in HDTV 1080p and 2 MP resolution**
- > **Built-in IR illumination for surveillance in total darkness**
- > **WDR to handle scenes with complex light conditions**
- > **PoE for network connectivity and electrical power**
- > **Optimized for reduced bandwidth and storage need**



## AXIS Companion Bullet mini LE

<b>Camera</b>		Typical 2.1 W, max 3.2 W	
Image sensor	1/2.8" progressive scan RGB CMOS	Connectors	T/100BASE-TX PoE
Lens	Horizontal field of view: 103° Vertical field of view: 55° Fixed iris and IR corrected	IR illumination	Power-efficient, long-life 850 nm IR LED. Range of reach up to 15 m (49 ft) depending on scene
Day and night	Automatically removable infrared-cut filter	Storage	AXIS Companion Recorder is required
Minimum illumination	0 lux with IR illumination on	Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–100% RH
Camera angle adjustment	Pan: +/-177° Tilt: 30° to 90° Rotation: 0°, 90°, 180°, 270° Can be directed in any direction	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Video</b>		Approvals	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, VCCI Class A, ICES-003 Class A, RCM AS/NZS CISPR 32 Class A Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66
Video compression	H.265 (MPEG-H Part 2)	Dimensions	Height: 127 mm (5 in) ø 100 mm (3 15/16 in)
Resolution	1920x1080 HDTV 1080p and 640x360	Weight	205 g (0.45 lb)
Frame rate	Up to 25/30 fps with power line frequency 50/60 Hz	Included accessories	Installation guide
Video streaming	Multiple, individually configurable streams Controllable frame rate	Optional accessories	AXIS T8415 Wireless Installation Tool AXIS T94B01P Conduit Back Box AXIS T91A27 Pole Mount For more accessories, see <a href="http://axis.com">axis.com</a>
Image settings	Color, brightness, sharpness, contrast, white balance, exposure control, rotation: 0°, 90°, 180°, 270°, including Corridor Format, privacy masks	Video management software	AXIS Companion available on <a href="http://axiscompanion.com/vms">axiscompanion.com/vms</a>
Wide dynamic range	WDR	Warranty	Axis 3-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>
<b>Network</b>		a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).	
Security	Password protection, HTTPS <sup>a</sup> encryption, digest authentication, user access log, signed firmware	Environmental responsibility: <a href="http://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a>	
Supported protocols	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , Bonjour, UPnP®, DNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP		
<b>System integration</b>			
Event triggers	Video motion detection		
<b>General</b>			
Casing	IP66, Plastic PC/ABS Color: white NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.		
Sustainability	PVC free		
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 1		