

AXIS Q6215-LE PTZ Network Camera

Heavy-duty PTZ camera with OptimizedIR

AXIS Q6215-LE PTZ Network Camera has a 1/2-inch sensor and combines great image quality with fast panning, tilting, and zooming. Its powerful, built-in IR illumination allows for an impressive viewing range in total darkness (up to 400 m or 1300 ft). This camera is ideal for open-area surveillance, since its robust design can withstand the toughest weather conditions including wind speed up to 245 km/h (150 mph). AXIS Q6215-LE is compliant with IP66, IP68, IK10, and NEMA 4X. It can be mounted facing up or down and comes equipped with a wiper to remove excess water, rain, or snow.

- > [HDTV 1080p with 30x zoom](#)
- > [Long-range OptimizedIR](#)
- > [MIL-STD-810G compliant](#)
- > [AXIS Guard Suite analytics](#)
- > [Zipstream, Lightfinder, and WDR](#)



AXIS Q6215-LE PTZ Network Camera

Camera		PTZ: PTZ preset, start/stop guard tour, autotracking Overlay text, day/night mode
Image sensor	1/1.9" progressive scan RGB CMOS	
Lens	Varifocal, 6.7–201 mm, F1.6–5.3 Horizontal field of view: 58.6°–2.2° Vertical field of view: 34.1°–1.2° Autofocus, automatic day/night	
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	Color: 0.07 lux at 30 IRE F1.6 B/W: 0.008 lux at 30 IRE F1.6, 0 lux with built-in IR illumination Color: 0.1 lux at 50 IRE F1.6 B/W: 0.01 lux at 50 IRE F1.6, 0 lux with built-in IR illumination	
Shutter time	1/30000 s to 1/6 s	
Pan/Tilt/Zoom	Pan: 360° endless, 0.05°/s to 150°/s Tilt: -90° to +90°, 0.05°/s to 150°/s Zoom: 30x optical zoom, 21x digital zoom Preset accuracy: 0.10° 256 preset positions, tour recording, guard tour, control queue	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC), H.264 Main, High and Baseline Profiles Motion JPEG	
Resolution	1920x1080 HDTV 1080p to 320x180	
Frame rate	Up to 60/50 fps (60/50 Hz) in all resolutions	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264	
Image settings	Saturation, brightness, sharpness, noise reduction, WDR, white balance, day-night shift priority, exposure mode, manual shutter time, defogging, backlight compensation, highlight compensation, compression, fine tuning of low-light behavior, text and image overlay, privacy masks	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management	
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP, NTCIP	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform, specifications at axis.com AXIS Guardian One-Click Connection ONVIF [®] Profile G and ONVIF [®] Profile S, specification at onvif.org	
Analytics	Included AXIS Video Motion Detection, AXIS Guard Suite including AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard, active tampering alarm, gatekeeper Supported Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	
Event triggers	Analytics, edge storage events, virtual inputs through API Detectors: day/night mode, live stream accessed, shock detection Hardware: fan, network, temperature Input Signal: virtual inputs, manual trigger PTZ: autotracking, error, moving, preset reached, ready Storage: disruption, recording System: system ready Time: use schedule	
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, and TCP	
Data streaming	Event data	
Built-in installation aids	Pixel counter Automatic orientation	
General		
Cybersecurity	Signed firmware	
Casing	IP66-, IP68-, NEMA 4X- and IK10-rated aluminum casing Color: urban grey NCS S 5502-B Wiper included (silicone wiper blade)	
Sustainability	PVC free	
Memory	1024 MB RAM, 512 MB Flash	
Power	High PoE 90 W midspan 1–port: 100–240 V AC, max 1.35 A Camera consumption: typical 25 W, max 71 W	
Connectors	RJ45 10BASE-T/100BASE-TX/1000BASE-T PoE	
IR illumination	Optimized IR with power-efficient, long-life 850 nm IR LEDs Range of reach 400 m (1300 ft) or more depending on the scene	
Storage	Support for SD/SDHC/SDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations, see axis.com	
Operating conditions	-50 °C to 50 °C (-58 °F to 122 °F) Absolute maximum temperature: 74 °C (165 °F) according to NEMA TS2 2016, 2.2.7 Arctic Temperature Control: Start-up as low as -40 °C (-40 °F) Humidity 10–100% RH (condensing) Wind load (sustained): 68 m/s (150 mph)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)	
Approvals	EMC EN 55032 Class A, EN 50121-4, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC/EN 62471 risk group 2 Environment IEC/EN 60529 IP66/IP68, NEMA 250 Type 4X, NEMA TS2 2016 (Subsection 2.2.7–2.2.9), IEC/EN 62262 IK10, MIL-STD-810G (Method 501.5, 502.5, 506.5, 509.5, 521.3), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 Network NIST SP500-267 Midspan: EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB	
Dimensions	210 x 330 x 313 mm (4 5/16 x 13 x 12 5/16 in)	
Weight	8.7 kg (19.3 lb)	
Included accessories	Installation Guide, Windows [®] decoder 1-user license, IK10 bumper, High PoE Midspan 1-port, RJ45 connector push pull plug	
Optional accessories	AXIS T95A64 Corner Bracket AXIS T98A15-VE Media Converter Cabinet A For more accessories, see axis.com	
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at axis.com/vms	
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty	

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eyay@cryptsoft.com).

Environmental responsibility:

axis.com/environmental-responsibility