

Axis High Power over Ethernet midspans & splitters

High Power over Ethernet for Axis PTZ & PTZ dome network cameras.



- > Reduced installation costs
- > Support for Axis PTZ and PTZ dome network cameras
- > IEEE 802.3at
- > IEEE 802.3af compliance

Axis High Power over Ethernet midspans and splitters offer an easy, fast and cost-effective solution for powering network video products – specifically PTZ (pan/tilt/zoom) and PTZ dome network cameras – without the need to install power outlets and electrical cabling.

Axis High Power over Ethernet (High PoE) midspans and splitters enable Axis network video products to receive data and power over the same Ethernet cable.

The High PoE products make it easier to install network video products in areas where power cabling and outlets are unavailable, thereby reducing installation costs.

These midspans and splitters are used to power network devices that require more power, as specified by the IEEE 802.3at standard. The midspans are also IEEE 802.3af compliant, meaning that they can be used with all Axis network video products with built-in PoE support.

The function of a midspan is to inject power into a network cable. A splitter, which separates data and power coming over an Ethernet cable, is used for a network video product without built-in support for PoE.

Technical Specifications – Axis High Power over Ethernet midspans

| Midspan | | General | |
|-------------------------|--|--------------------------------------|--|
| Model | AXIS T8123 High PoE 30 W Midspan 1-port AXIS T8124 High PoE 60 W Midspan 1-port | Display and indicators | Port interfaces are located on the front panel System indicator: AC power Channel indicator: power For more information, see www.axis.com/techsup |
| Function | Data and power are fed to a network video product through an Ethernet cable; use together with a High PoE splitter for a network video product without built-in PoE support | Compliance | IEEE 802.3at, IEEE 802.3af, RoHS, WEEE, CE |
| Data rate | 10/100/1000 Mbps | Mounting | Wall or shelf mounting |
| Data & Power | | Approvals | FCC Part 15, Class B with FTP cabling CE: EN 55022 Class B (Emissions), EN 55024 (Immunity), VCCI Safety: CB, UL/cUL per EN 60950-1, GS Mark per EN 60950-1, KCC, UL-AR |
| Connectors | Shielded RJ-45, EIA 568A and 568B | Operating conditions | AXIS T8123: 0 – 40° C (32 – 104°F) Humidity max. 95% RH (non-condensing) AXIS T8124: -10 – 45°C at 60W (14 – 113°F) -10 – 55°C at 30W (14 – 131°F) Humidity max. 95% RH (non-condensing) |
| Network cables | Shielded category 5 (or higher) | Dimensions (HxWxD) and weight | 51.3 x 87.9 x 166 mm (2.0" x 3.46" x 6.53") AXIS T8123: 350 g (0.771 lbs) AXIS T8124: 400 g (0.881 lbs) |
| Wiring | Data provided over pairs 1/2 and 3/6 for 10/100 Ethernet, over all four pairs for Gigabit Ethernet Power over spare pairs 4/5 (+) and 7/8 (-) | Installation and management | Plug-and-play installation; automatically detects PoE and High PoE-enabled devices and supplies inline power Local LED management display |
| Output power | AXIS T8123: 55 V DC (max. 30 W) AXIS T8124: 54–57 V DC (max. 60 W) | | |
| Input power | AXIS T8123: AC Input Voltage: 100 to 240 V AC (max. 37 W) AC Frequency: 50 – 60 Hz AXIS T8124: AC Input Voltage: 100 to 240 V AC (max. 74 W) AC Frequency: 50 – 60 Hz | | |

Technical Specifications – Axis High Power over Ethernet splitters

| Splitters | | General | |
|-------------------------|--|--------------------------------------|---|
| Models | AXIS T8126 High PoE Splitter 12V AXIS T8128 High PoE Splitter 24V | Compliance | WEEE, CE |
| Function | Separate data and power coming over a network cable for a network video product without built-in PoE support | Operating conditions | 0 – 40° C (32 – 104°F) Humidity max. 90% RH (non-condensing) |
| Data & Power | | Approvals | FCC Part 15 Class A FTP, Class A UTP EN55022 (CISPR 22) Class A Immunity EN55024 (CISPR 24) |
| Connectors | Data & power in: Shielded RJ 45 Data out: Shielded RJ-45 Power out: DC barrel connector; with '+' centered | Dimensions (HxWxD) and weight | 94 x 31 x 73 mm (3.7" x 1.12" x 2.87") 112 g (0.247 lbs) |
| Output current | AXIS T8126: 2 A at 12 V DC AXIS T8128: 1 A at 24 V DC | Included accessories | AXIS T8126 – cable adapters for AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 225FD, AXIS 210, video encoders AXIS T8128 – cable adapter for AXIS 231D+, AXIS 232D+, AXIS 233D For a complete list of supported products, please refer to www.axis.com/products/pol/high_poe/supported.htm |
| Input power | max. 30 W | | |
| Installation | Plug-and-play installation between midspan and camera | | |

More information is available at www.axis.com

System overview

