

PT IR Illuminator Kit A

Suitable for AXIS Q87 Series

A tailor-made infrared illuminator kit for AXIS Q87 Dual PTZ Network Camera Series. The illuminators enhance identification capabilities during nighttime. The kit contains one 10-degree and one 50-degree illuminator, which together cover the field of view of the camera when zoomed in or out. The approximate range of coverage is between 50 to 100 meters (55 to 109 yards). Moreover, it includes a mount bracket to facilitate the positioning of the units and a built-in adjustable photocell. PT IR Illuminator Kit A supports IP66 protection rating against the ingress of dust and high-pressure water jets from any direction.

- > **Outdoor-ready infra-red illuminators**
- > **Suitable for AXIS Q87 Series**
- > **IR-LED 10° angle and IR-LED 50° angle**
- > **Protection against ingress of water and dust**



PT IR Illuminator Kit A

Models	IR-LED 10° angle IR-LED 50° angle	Approvals	EN 55022 Class A, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, RCM AS/NZS CISPR 22 Class A, EN 60950-1, EN 60950-22, IEC/EN 60529 IP66, EN 62471
Supported cameras	AXIS Q8721-E AXIS Q8722-E	Operating conditions	-50 °C to 50 °C (-58 °F to 122 °F)
Angle	10° to 50°	Dimensions	180 x 135 x 67 mm (7 1/16 x 5 5/16 x 2 5/8 in)
Distance	IR-LED 10°: 100 m (328 ft) IR-LED 50°: 50 m (164 ft)	Weight	1.4 kg (3.1 lb)
Control technology	Power level, Photocell sensitivity, Telemetry link for remote activation (if required)	Included accessories	U-bracket, In-built adjustable photocell
Input power	12-24 V AC/DC, 35 W	Warranty	Axis 1-year warranty, see www.axis.com/warranty
Cable length	70 cm (2.3 ft)		
Casing	IP66-rated		

More information is available at www.axis.com