

ATM-ENC6-R6 way 19" Rack Mounting ATM EncoderATM-ENC12-R12 way 19" Rack Mounting ATM EncoderATM-ENC6-D6 way Desktop ATM Encoder



FEATURES

- Real-time compression
- Supports full frame rate
- Dual standard PAL/NTSC
- · Audio input and output
- · Direct interface to telemetry receiver

OVERVIEW

The ATM Video Encoder allows an analogue video signal to be digitally encoded, wavelet compressed, and transmitted on the ATM network. It can simultaneously transmit a full-motion picture for display on a monitor and a reduced frame rate picture for recording by a Digital Video Recorder. Up to 6 composite video inputs, or three S-Video, are supported.

The Encoder is available as a desktop unit and in a 1U high 19" rack mounted enclosure that has space for two Encoders. Audio support consists of one stereo or two mono audio channels in each direction; inputs are digitised and transmitted on the network, and incoming digital audio is converted to analogue signals on the outputs.

The RS422 port may be used for direct connection of a Destiny telemetry receiver or to convey commands to other equipment such as an analogue video matrix.

SPECIFICATIONS

Supply voltage Power consumption Mains Frequency	120-240V AC (Auto-ranging) (Range 88 to 132V; 176 to 264V) 25W 50/60Hz (Auto-ranging) (Range 47 - 63Hz)
VIDEO Format Video sizing Video perfromance	PAL (50Hz) or NTSC (60Hz) selectable Uses wavelet compression technology to provide various scaled pictures PAL up to 50fps NTSC up to 60fps PAL up to 720 x 576 pixels
Digital Audio	NTSC up to 720 x 486 pixels 16-bit A-Law or u-Law (stereo/mono) formats. Sampling rate from 8kHz to 44.1kHz (CD) and 48kHz (DAT)
Rate control	Software configurable cell pacing for ATM output streams to ensure traffic compliance
ATM Protocols	AAL5 for all video data; AAL0.1 or 5 for audio and control data
ATM Connection	RJ45, 100mS, 25Mbps, UTP
Dimensions	1 U 19 inch metal unit that can be optionally expanded to house 2 Video Encoders,
Weight	482 x 138 x 44 mm. Single Encoder Desktop Unit 305 x 140 x 51mm Single: 2.3kg
Colour	Double:2.6kg Graphite Grey

