



### **Application Notes**

The Starcard provides a simple and cost-effective solution in the installation of RS485/422 telemetry systems. The Starcard takes RS485/422 data from one source and distributes it across 8 isolated outputs which can be wired in a star format or allow up to 31 cameras to be daisy chained. 8 RS422/485 outputs to allow star wiring of telemetry systems and Tx1500 Key boards and alarm Cards can also be used when star wiring is required for other systems

#### **Features**

- Two RJ45 sockets and a screw terminal connector for RS485/422 input from a controller and output to additional daisy chained Starcards
- Eight screw terminal connectors used to output RS485/422 data. Each output can be connected to a single dome / receiver or up to 31 domes / receivers or a combination wired as a daisy chain.
- Can be used with either 2-wire, half duplex; 4-wire, full duplex or simplex systems
- Can also be used with simplex RS485/422 links, for example the RS485 output of multiplexers.
- DB9F connector provides a diagnostic output. This can be used with a laptop PC to monitor the data being sent out of the Starcard via RS232



## **Building Block Video Ltd**

17 Apex Park, Diplocks Way, Hailsham, East Sussex, BN27 3JU, UK Tel: +44 (0) 1323 842727 Support: +44 (0) 1323 444600

Fax: +44 (0) 1323 842728 www.bbvcctv.com





# **Technical specification**

**Power Supply** 

**Inputs** 

**Outputs** 

**Other outputs** 

**Features** 

Installation

**Dimensions** 

Weight

Colour

9 - 12 Vdc 500mA

2-wire RS485/422 Simplex

4-wire RS422 Full Duplex

• 8 x 2 or 4-wire RS485 (switch selectable – default 4-wire).

 Maximum cable runs approx. 1200mtrs. When the domes / receivers are wired as a daisy chain, the last unit must be terminated and the intermediate units must be unterminated. With a single dome connected to each output, the BBV

RS485/422 must be terminated

RS232 monitor output via chassis mounted DB9 connector

LED as power indicator

 Supplied in 1U 19in rack mountable metalwork or wallmounted via the fixing brackets supplied

Width 427mm Depth 73mm Height 45mm

2.2Kg

Metal case powder coated RAL7035



## **Building Block Video Ltd**

17 Apex Park, Diplocks Way, Hailsham, East Sussex, BN27 3JU, UK Tel: +44 (0) 1323 842727 Support: +44 (0) 1323 444600

Fax: +44 (0) 1323 842728 www.bbvcctv.com