

Essential and Capable Pro-Lite Micro Access Control Server

The pro-lite BCDM02P-ACS access control micro server packs a full scale server horse power into a small form factor. Despite its size, this server is engineered to meet the same data processing and storage demands as larger sized servers.

The Intel® Core® 7th generation processor will handle multiple concurrent processor intensive tasks with capacity to spare. Experience fast startup and application loading with the dedicated solid state operating system and Application drive. An additional 1TB of 24/7 duty cycle grade storage drive provide more than ample storage capacity in a small form factor.

Require backwards compatibility to legacy serial devices? The BCDM02P-ACS's multiple USB ports support the connection of user interfaces and legacy devices. Peace of mind is provided with the BCDVideo five-year, next business day on-site, Keep Your Hard Drive warranty.



— POWERED BY —
DELL EMC

KEY FEATURES

- Intel® Core® i7 7th Gen Processor Family
- Throughput Optimized OS SSD
- Operating Systems Supported:
 - Windows 10 Pro



I/O Performance Optimized



SSD & 24/7 Duty Cycle SATA Drives



Five-Year On-site Warranty
***Keep Your Hard Drive**



Intel® Core® i7 Processor

CERTIFIED | PURPOSE BUILT | GUARANTEED

SYSTEM	
Processor(s)	Up to (1) Intel® Core® 7th Generation Processor Product Family
Operating Systems Supported	Windows 10 Pro
Operating System Drive(s)	(1) 256GB SSD
Storage Drive(s)	(1) 1TB 24/7 Duty Cycle SATA Drive
Memory	16GB Standard, Up to 32GB RAM (2 x DDR4 DIMMs RAM)
Networking	(1) 1GbE
USB(s)	Rear (2) USB 3.1 Gen 1, (2) USB 2.0; Front (2) USB 3.1 Gen 1
Graphics Card	Intel Embedded Graphics HD 630
Video Outputs	(1) DisplayPort (1) HDMI
Manufacturer	BCDVideo
Warranty	Global 5-Year 24/7 Support, NBD On-site, Keep Your Hard Drive
MECHANICAL	
Form Factor	Micro
Hard Drive Bays	(1) M.2; (1) 2.5"
Hard Drives Supported	SSD & SATA
Power Supply(s)	(1) 65W 100-240VAC
Operating Temperature	(Min) 50°F - (Max) 95°F [(Min) 10°C - (Max) 35° C]
Operating Humidity	5 ~ 90% (non-condensing)
Dimensions (WxDxH)	1.4" x 7.0" x 7.2" (36mm x 178mm x 182mm)
Max. Weight	2.6 lbs (1.18 kb)
Regulatory	IEC 60950-1, European Norm EN 60950-1, CISPR 22/CISPR 24, EN55022/55024