

# TITAN NETWORKING SERIES

## SIMPLE, UNICAST NETWORKING

### TTN-3526 FAMILY

#### KEY FEATURES



**PORT DENSITY:**  
26 PORTS



**LIMITED LIFETIME**



**STACKABLE CHASSIS**



**UNICAST NETWORKING**



#### VERTICAL MARKETS:

A cost-effective, simple setup solution, the BCD-TTN-3526 provides stackable unicast switches. The series is perfectly suited to the unique requirements of the security market.



The Titan Networking Series is a series bringing simple, enterprise networking solutions for your security project. Powered by Avaya Networking, the 3526 Family offers a 24 port, stackable solution. The BCD-TTN-3526 is designed in mind for smaller projects with compact solutions. Built for unicast networking, these switches also have a limited lifetime warranty and 24/7 phone support. BCDVideo and Avaya - bringing simple solutions to the security market.

	RJ45 PORTS	COMBO SFP PORTS	FANLESS OPERATION	WEIGHT	INPUT CURRENT (MAX)
<b>BCD-TTN-3526</b>	24 Gigabit ports	2 Combo 10/100/1000BASE-T or SFP Ports	Available	8 lb/3.60 kg	.028@100VAC
<b>BCD-TTN-3526-POE+</b>	24 Gigabit ports PoE+	2 Combo 10/100/1000BASE-T or SFP Ports	Not Available	10 lb/4.50 kg	5.0A@100VAC

	POWER CONSUMPTION	THERMAL RATING (OUTPUT)	MAXIMUM PoE BUDGET	MTBF	UPC
<b>BCD-TTN-3526</b>	28.5 Watts (max)	65 BTU/hr (max)	N/A	645,510 hrs	859407006104
<b>BCD-TTN-3526-POE+</b>	500 Watts (max)	360 BTU/hr (max)	370 Watts	332,778 hrs	859407006111

# TITAN NETWORKING SERIES

## SIMPLE, UNICAST NETWORKING

<b>SYSTEM CPU SPEED</b>	<b>SYSTEM MEMORY</b>	<b>INPUT POWER</b>	<b>SWITCH FABRIC PERFORMANCE</b>	<b>FRAME FORWARDING RATE</b>
400MHz	32MB Flash, 128MB DRAM	100-240VAC	12.8Gbps	9.5Mpps
<b>REAR STACKING</b>	<b>CHASSIS</b>	<b>HEIGHT</b>	<b>WIDTH</b>	<b>DEPTH</b>
Capable	1U Rackmount	1.75"/44.5 mm	17.5"/440 mm	11"/280 mm

<b>ENVIRONMENTAL SPECIFICATIONS</b>	<b>SAFETY AGENCY APPROVALS</b>
Operating Temperature: 32° and 122° F (0° and 50° C) Operating Altitude: 10,000 ft Storage Temperature: -40C to 70C Storage Altitude: 10,000 ft Acoustic Noise (db): up to 58 (0 for Fanless models) Operating Humidity: 95% RH non-condensing Storage Humidity: 95% RH non-condensing	IEC 60950 International CB Certification EN 60950 European Certification UL60950 US Certification CSA22.2, #60950 Canadian Certification NOM Mexican Certification