

# BP0022-POE

## POE IP Camera IP66 Outdoor Housing



Bolide PoE Camera Enclosure is designed for Bolide iPac series camera. Using Power-over-Ethernet (PoE) not only reduces the cost of installation and provide easy single UTP connection for your both power and data. With the convenience RJ45 port on the bottom of the enclosure, allows easy installation of Power-over-Ethernet into the enclosure quick and cost-effectively.

Standard features for Bolide PoE IP Camera Enclosure includes: wall mount, heater and fan. Constructed from die-cast aluminum and UV rated Glass. Special locking system ensure proper the max security for your IP Cameras or iPac Cameras.

**iPac™**  
Compatible

**CE** **FC**

### Features:

- POE standard meets IEEE-802.3af and IEEE2.3at
- Back Locking Latch
- Diecast Aluminum Construction
- Ideal for In/Outdoor Applications
- Extremely ease for Installation and Service
- IP66 Rated
- Long life expectancy Heater/Fan
- PoE Connections Inside Enclosure



### Specification:

<b>Model Number</b>	<b>BP0022-POE</b>
Exterior Dimension	17(L) x 5(H) x 6(W)
Interior Dimension	9(L) x 3.5(H) x 4(W)
Housing Security	Available, back locking latch
POE	POE 802.3af 48V DC standard
Housing Bracket	Included
Bracket Size	11(L) x 3.25(H) x 4(W)
Heater	Automatic Thermal Sensor On (40°F) Off (60°F)
Blower	Automatic Thermal Sensor On (105°F) Off (78°F)
Ethernet Speed	10/100/1000Mbs

For more information or technical support, please call (909) 305-8889 or log on to [www.bolideco.com](http://www.bolideco.com)

468 South San Dimas Avenue, San Dimas CA 91773 | Tel: (909) 305-8889 Fax: (909) 305-0999

Bolide Technology Group makes no representation concerning the legality of certain product application. We encourage you to check and comply with all applicable local state, and federal laws. Specification and availability are subject to change without notice. All trademarks, registered trademarks, and names are the property of their respective owners.