

D1250 Battery (12 V, 5 Ah)

www.boschsecurity.com



BOSCH
Invented for life



- ▶ 12 VDC sealed lead-acid
- ▶ Fully rechargeable
- ▶ Maintenance-free
- ▶ For use as secondary power for accessory modules
- ▶ Long service life

A 12 V sealed lead-acid battery. It acts as a maintenance-free standby and auxiliary power supply that provides long service life and dependability. Use the battery only with charging circuits calibrated for lead-acid batteries. It is suitable for supplying backup power for fire, security, and access control systems during AC power failures.

Certifications and approvals

Region	Certification
Europe	CE Council Directive 89/336/EEC Electromagnetic Compatibility

Installation/configuration notes

Standby Power Requirements

Refer to the appropriate control panel installation manual for information on calculating the standby battery requirements for the system. Total continuous and intermittent current requirements must not exceed the amp hour capacity of the battery.

Technical specifications

Physical Specifications

Nominal Voltage:	12 V
Nominal Capacity (20 Hour)	5 Ah
Weight:	1.85 kg (4 lb)
Dimensions:	10 cm x 9 cm x 7 cm (4 in. x 3.5 in. x 2.8 in.)
Height with Terminals:	10.6 cm (4.2 in.)
Standard Terminal:	FI-Faston Tab No. 187

Capacity

20 Hour rate (0.25 A):	5 Ah
10 hour rate (0.45 A):	4.5 Ah
5 hour rate (1 A):	4 Ah
1 hour rate (5 A):	3 Ah

Capacity Affected by Temperature

40°C (104°F):	105%
30°C (68°F):	100%
0°C (32°F):	85%

Constant Voltage Charge

Cycle:	Initial charging current less than 1.3 A. Voltage 7.20 V to 7.50 V at 20°C (68°F). Temperature Coefficient -15 mV/C.
Standby:	Initial charging current less than 1.26 A. Voltage 6.75 V to 6.90 V at 20°C (68°F). Temperature Coefficient = 10 mV/C.

Ordering information**D1250 Battery (12 V, 5 Ah)**

A 12 V sealed lead-acid battery for standby and auxiliary power. Suitable for supplying backup power for fire, security, and access control systems during AC power failures.

Order number **D1250**

Represented by:**Americas:**

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com