DIVAR IP all-in-one 7000 2U

www.boschsecurity.com





The DIVAR IP all-in-one 7000 family is an affordable, simple and reliable all-in-one recording, viewing and management solution for network surveillance systems of up to 256 channels (with 8 channels pre-licensed). Running the full BVMS solution and powered by Video Recording Manager software from Bosch, DIVAR IP all-in-one 7000 is an intelligent IP video management and storage device.

DIVAR IP all-in-one 7000 2U is a 2U rack mount unit that combines advanced management and state-of-theart recording management into a single cost-effective, plug-and-play IP recording appliance for IT-minded customers.

System overview

The DIVAR IP all-in-one 7000 family utilizes an energy efficient, embedded design which reduces possible points of failure and boasts Bosch quality through-andthrough. Utilizing "enterprise-rated" hard drives in a fault tolerant RAID-5 configuration, dual port Gigabit Ethernet network interface, 8 GB system memory and an Intel Xeon Quad Core Processor, the device delivers high-end performance at a very affordable price. Easy to install and operate, the system features wizard-based set-up and centralized configuration. All components are pre-installed. Simply connect to the



- RAID-5 protected (standard configuration), all-in-one video management solution for up to 256 channels
- Out-of-the-box IP video management solution with up to 96 TB storage capacity
- Instantly find what you are looking for
- Advanced user and alarm management
- 3 years warranty, including next business day services

network and power the unit up - DIVAR IP all-inone 7000 is ready to begin recording straight out of the box.

BVMS manages all IP and digital video and audio, plus all the security data being transmitted across your IP network. It seamlessly combines IP cameras and encoders, provides system-wide event and alarm management, system health monitoring, user and priority management.

Functions

The DIVAR IP all-in-one 7000 2U units feature highly energy-efficient hot-swap redundant power supplies, as well as front-swappable SATA-3 hard drives providing up to 96 TB of gross storage capacity. All system software is pre-installed - creating an out-ofthe-box ready-to-use video management appliance. The DIVAR IP all-in-one 7000 2U units utilize Microsoft Windows Storage Server 2016.

Instant real time access to video

View high quality HD and even UHD video despite low or limited bandwidth connections. Dynamic Transcoding technology ensures you can view your video immediately - anytime, anywhere. The built-in transcoder supports up to 4 x UHD resolution H.264 video streams in parallel.

Management

Once booted up the system will offer immediate access to the BVMS management application via a customized GUI. The ability to use one central GUI for configuration and operation management reduces installation and training requirements, and helps keep ongoing system management costs low.

Remote viewing

For remote viewing of a single DIVAR IP all-in-one 7000 system, BVMS Operator Client is included. For multiple systems, add them to BVMS Enterprise Management Server.

Alternatively, use Video Security Client for viewing video from a separate workstation or mobile device.

IT Management

Microsoft Windows Storage Server 2016 provides a simple, intuitive user interface for system configuration and unified appliance management. Administrators and IT professionals will appreciate the ability to manage DIVAR IP all-in-one 7000 systems using the built-in Microsoft System Center Suite. The ability to use one central tool for configuration and operations management reduces installation and training requirements, and helps keep ongoing system management costs low.

In addition, the DIVAR IP all-in-one 7000 system offers advanced monitoring and management options using the Intelligent Platform Management Interface (IPMI).

Monitoring

The DIVAR IP all-in-one 7000 family provides SNMP, Remote Desktop and HTTP monitoring support for the system's hardware and for the video management applications.

Increased reliability of high-availability hardware, embedded design as well as system-wide monitoring and management ensure maximum uptime.

Certifications and approvals

Region	Regulato	ory compliance/quality marks
Europe	CE	DIVAR IP all-in-one 7000

Installation/configuration notes



Environmental conditions

Install the system in a clean, dust-free, dry and weather-protected area that is well ventilated. Avoid areas where heat, electrical noise and electromagnetic fields are generated. The standard warranty coming with the system will be void if evidence is seen that the system was exposed to conditions contradicting the environmental conditions mentioned here.

System status

DIVAR IP all-in-one 7000 units come fully loaded and fully functional with Microsoft Operating System and Bosch applications:

- Windows Storage Server 2016, 64-bit
- BVMS
- Video Recording Manager including
- Video Streaming Gateway Dynamic Transcoding
- Dynamic Hanseoung

Third-party hard drives

DIVAR IP all-in-one 7000 units without pre-installed hard drives:

The RAID configuration of third-party data hard drives must be set up manually via the pre-installed RAID management utility. Only after this manual RAID configuration the DIVAR IP all-in-one 7000 system provides full functionality.

RAID configuration

DIVAR IP all-in-one 7000 2U units come pre-configured in a RAID-5 standard configuration with iSCSI LUNs (fully populated system only) and provide the following specifications:

RAID-5 configuration

Gross Capacity	Net Capacity	Bandwidth*	IP Cameras
w/o HDD	n/a	550 Mbit/s	256 max.
8 x 4 TB	26068 GB	550 Mbit/s	256 max.
8 x 8 TB	52136 GB	550 Mbit/s	256 max.
8 x 12 TB	78204 GB	550 Mbit/s	256 max.

*Performance only warranted with hard drive models tested and qualified by Bosch.

These values refer to the BVMS recording engine; Net capacity for a RAID-5 configuration without hot spare; 256 connected IP cameras indicate the number of concurrent recordable cameras plus 8 sessions for replay.

Optional supported RAID configurations are RAID-5 with 1 x hot spare or RAID-6 without hot spare. The optional RAID configurations will not come preconfigured but must be set up manually via the preinstalled RAID configuration utility.

RAID-5 plus hot spare configuration

Gross Capacity	Net Capacity	Bandwidth*	IP Cameras
w/o HDD	n/a	550 Mbit/s	256 max.
8 x 4 TB	22344 GB	550 Mbit/s	256 max.
8 x 8 TB	44688 GB	550 Mbit/s	256 max.
8 x 12 TB	67032 GB	550 Mbit/s	256 max.

*Performance only warranted with hard drive models tested and qualified by Bosch.

RAID-6 configuration

Gross Capacity	Net Capacity	Bandwidth*	IP Cameras
w/o HDD	n/a	550 Mbit/s	256 max.
8 x 4 TB	22344 GB	550 Mbit/s	256 max.
8 x 8 TB	44688 GB	550 Mbit/s	256 max.
8 x 12 TB	67032 GB	550 Mbit/s	256 max.

*Performance only warranted with hard drive models tested and qualified by Bosch.

Operation modes

DIVAR IP all-in-one 7000 units can operate in three different modes:

• Full video recording and management system, utilizing the BVMS and Video Recording Manager core components and services. This mode allows for advanced video management features such as event and alarm handling.

A base license with 8 included camera channels is already pre-licensed.

You can expand the system up to 32 channels with a MBV-BPLU-DIP license and further up to 256 channels with additional 1-channel licenses (MBV-1CHAN-DIP). The recorded video streams need to be configured in a way that the maximum bandwidth of the system (BVMS/Video Recording Manager base system plus iSCSI storage expansions) is not exceeded.

- Pure video recording system, utilizing the Video Recording Manager core components and services. In this mode 64 Video Recording Manager camera-recording channels are already pre-licensed. You can expand the system up to 256 channels with the Video Recording Manager channel licenses listed in the ordering information. The recorded video streams need to be configured in a way that the maximum bandwidth of the system (BVMS/ Video Recording Manager base system plus iSCSI storage expansions) is not exceeded.
- iSCSI storage expansion for a BVMS or Video Recording Manager system, which runs on a different hardware. Up to four of these iSCSI storage expansions can be added to a BVMS or Video Recording Manager system running on a DIVAR IP all-in-one 7000 unit.

License limitations

For the BVMS licenses applied on DIVAR IP all-inone 7000 units, please note the upper limit of each:

Pre-licensed	Upper limit
2	10
1	10
2	10
1*	4*
1	10
	2 1 2

*Mobile Video Service needs to run on separate hardware

For further details, see the respective license information.

i Notice

Uninterruptable Power Supply (UPS). We strongly recommend using an "Online UPS" with an always active battery. The UPS must support Microsoft Windows Storage Server 2016 and must be sufficient to allow time to bring an auxiliary power source on line, or to properly shut down the DIVAR IP disk array(s).

i Notice

Bosch is not liable for system failures of units equipped with third-party hard drives if the thirdparty hard drives are source of the issues. Such drives are not covered by the 3 years warranty.

Notice

i

The next business day on-site service level can only be provided if the respective system has been registered immediately after receipt and installation. Otherwise, service will be provided based on best effort basis.

Information about registration details is available in every shipment (registration form) or from the Bosch online product catalog.

Next business day services cannot be provided in every country everywhere. For limitations and exceptions see the registration details in the registration form.

Technical specifications

Electrical

AC input rating	100 to 240 V / 50 to 60 Hz	
Electrical 140 VAC input		
Input current	2.4 A	
Actual output wattage	305.6 W	

Actual output wattage from power supply	305.6 W
Efficiency of power supply	92%
Power consumption*	332.2 W
Total BTU/h	1133.9
Power factor	0.98
System AC input VA requirement	339.0 VA

*System power consumption may vary based on workload and environment.

Electrical 240 VAC input	
Input current	1.4 A
Actual output wattage from power supply	305.6 W
Efficiency of power supply	94%
Power consumption*	325.1 W
Total BTU/h	1109.7
Power factor	0.96
System AC input VA requirement	338.7 VA

*System power consumption may vary based on workload and environment.

Mechanical		
Form factor	2HU rack mount	
Power supply	740 W Platinum Level Redundant	
USB ports	Front: 2 USB 2.0 ports Rear: 2 USB 2.0 ports, 2 USB 3.0 ports	
Network	Dual Intel i210AT Gigabit LAN (teamed) 1 IPMI BMC port	
Dimensions (H x W x D)	89 x 437 x 648 mm (3.5 x 17.2 x 25.5 in)	
Weight	23.6 kg (52 lb)	
Environmental		
Operating temperature	+10 °C to +35 °C (+50 °F to +95 °F)	
Non-operating temperature	-40 °C to +70 °C (-40 °F to +158 °F)	
Operating relative humidity	8 to 90% (non-condensing)	
Non-operating relative humidity	5 to 95% (non-condensing)	
Processor		
Processor	Intel Xeon Processor E3-1275 V3 (8 MB Cache, 3.5 GHz)	
Socket	1	
Cache memory	8 MB Intel Smart Cache	
Memory protection	ECC unbuffered	
Max front side bus	1600 MHz	
Memory		
Memory installed	8 GB, DDR3-1666 ECC UNB (1 x 8 GB)	

Storage	
Storage Type	8 Trays: 3.5-inch SATA
Hard Drives Installed	
• Data	SATA-3, 7200 RPM, 64 MB, 3.5", RAID-5 configuration(default) DIP-7284-8HD: 8 x 4 TB DIP-7288-8HD: 8 x 8 TB DIP-728C-8HD: 8 x 12 TB DIP-7280-00N: w/o HDD
• OS	2 x 120 GB SSD RAID-1 configuration
SAS RAID Card	8 ports LSI 3108 SAS3 controller
DVD writer	Internal

Ordering information

DIP-7284-8HD Management appliance 2U 8X4TB

All-in-one recording, viewing and management solution for network surveillance systems. With 8 x 4 TB storage capacity. Order number **DIP-7284-8HD**

EWE-7184S8H-IW DIP-7184-8HD SRV Ext. 12 Mths IW

12-month hardware service extension next business day for DIP-7184-8HD or DIP-7284-8HD, available for a 4th or a 4th and 5th year as a standard. Order number **EWE-718458H-IW**

DIP-7288-8HD Management appliance 2U 8X8TB

All-in-one recording, viewing and management solution for network surveillance systems. With 8 x 8 TB storage capacity. Order number **DIP-7288-8HD**

EWE-7188S8H-IW DIP-7188-8HD SRV Ext. 12 Mths IW

12-month hardware service extension next business day for DIP-7188-8HD, DIP-7288-8HD or DIP-728C-8HD, available for a 4th or a 4th and 5th year as a standard. Order number **EWE-7188S8H-IW**

DIP-728C-8HD Management appliance 2U 8X12TB

All-in-one recording, viewing and management solution for network surveillance systems. With 8 x 12 TB storage capacity. Order number **DIP-728C-8HD**

EWE-7188S8H-IW DIP-7188-8HD SRV Ext. 12 Mths IW

12-month hardware service extension next business day for DIP-7188-8HD, DIP-7288-8HD or DIP-728C-8HD, available for a 4th or a 4th and 5th year as a standard. Order number **EWE-718858H-IW**

DIP-7280-00N Management appliance 2U without HD All-in-one recording, viewing and management solution for network surveillance systems. Without HDD. Order number **DIP-7280-00N**

EWE-7180S0N-IW DIP-7180-00N SRV Ext. 12 Mths IW

12-month hardware service extension next business day for DIP-7180-00N or DIP-7280-00N, available for a 4th or a 4th and 5th year as a standard. Order number **EWE-718050N-IW**

Accessories

DIP-7GRSN-P6 Graphic / sound for DIPaio7000 Graphics card (Nvidia Quadro P620 or successor) and sound card for DIVAR IP all-in-one 7000 appliances. Order number **DIP-7GRSN-P6**

DIP-AIO4-HDD 4TB HDD DIVAR IP all-in-one Hard disk storage expansion for DIVAR IP all-in-one appliances with a capacity of 4 TB. Order number **DIP-AIO4-HDD**

DIP-AIO8-HDD 8TB HDD DIVAR IP all-in-one

Hard disk storage expansion for DIVAR IP all-in-one appliances with a capacity of 8 TB. Order number **DIP-AI08-HDD**

DIP-AIO12-HDD 12TB HDD DIVAR IP all-in-one

Hard disk storage expansion for DIVAR IP all-in-one appliances with a capacity of 12 TB. Order number **DIP-AI012-HDD**

KBD-UXF Keyboard, USB CCTV-oriented

USB CCTV-oriented keyboard for use with BVMS, BIS -Video Engine, or DIVAR IP systems. Order number **KBD-UXF**

Software Options

MBV-1CHAN-DIP License Camera/decoder expansion

BVMS license for DIVAR IP all-in-one.

Expansion license for 1 channel (cameras/decoders). The use with DIVAR IP all-in-one 5000 requires a MBV-BLIT-DIP license.

The use with DIVAR IP all-in-one 7000 requires a MBV-BPLU-DIP license.

Order number MBV-1CHAN-DIP

MBV-BPLU-DIP License Plus base for DIP AIO 6000-7000

BVMS Plus license for DIVAR IP all-in-one 6000 and DIVAR IP all-in-one 7000.

Expansion license to expand to 32 channels (cameras/ decoders).

Order number MBV-BPLU-DIP

MBV-1DUR-DIP License Camera dual recording expansion

BVMS license for DIVAR IP all-in-one.

Expansion license for 1 encoder channel used for dual recording.

Order number MBV-1DUR-DIP

MBV-1FOV-DIP License VRM Failover channel expansion

BVMS license for DIVAR IP all-in-one. Expansion license for 1 encoder channel used with a Failover VRM. Order number MBV-1FOV-DIP

MBV-XWST-DIP License Workstation expansion

BVMS license for DIVAR IP. Expansion license for 1 workstation (each extra workstation requires 1 license). Order number MBV-XWST-DIP

MBV-XDVR-DIP License DVR expansion

BVMS license for DIVAR IP.

Expansion license for 1 DVR. Order the exact number required.

Order number MBV-XDVR-DIP

MBV-XKBD-DIP License Keyboard expansion BVMS license for DIVAR IP. Expansion license for 1 CCTV keyboard. Order the exact number required. Order number MBV-XKBD-DIP

MBV-XMVS-DIP License Mobile video service expansion

BVMS license for DIVAR IP. Expansion license for 1 Mobile Video Service. Order number MBV-XMVS-DIP

MBV-XINT-DIP License Intrusion panel expansion

BVMS license for DIVAR IP. Expansion license to integrate intrusion panels. Order number MBV-XINT-DIP

MBV-XPI-DIP License Person ident. channel expansion

Expansion license for 1 person identification channel. Order the exact number required. Order number MBV-XPI-DIP

MVM-XVRM-016 16 camera Upgrade License

Video Recording Manager upgrade license. For 16 cameras. Order number MVM-XVRM-016

DLA-XVRM-032 AIO - 32 camera Upgrade License

Video Recording Manager upgrade license. For 32 cameras. Order number DLA-XVRM-032

DLA-XVRM-064 AIO - 64 camera Upgrade License

Video Recording Manager upgrade license. For 64 cameras.

Order number DLA-XVRM-064

Represented by:

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 emea.securitysystems@bosch.com emea.boschsecurity.com

Germany: Bosch Sicherheitssysteme GmbH Robert-Bosch-Ring 5 85630 Grasbrunn German www.boschsecurity.com

North America: Bosch Security Systems, LLC 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 onlinehelp@us.bosch.com www.boschsecurity.us

Asia-Pacific:

Robert Bosch (SFA) Pte Ltd. Security Systems 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2699 apr.securitysystems@bosch.com www.boschsecurity.asia

© Bosch Security Systems 2020 | Data subject to change without notice 66038919947 | en, V4, 25. Aug 2020