



BOSCH
Invented for life

LTC 2009, LTC 2012, and LTC 2017 Series Monochrome Video Monitor



- ▶ Choice of 23-, 30- and 43 cm (9-, 12- and 17 in.) monitors
- ▶ High quality pictures
- ▶ Auto-termination
- ▶ Supply 100-230 VAC with selectable selection between EIA and CCIR formats
- ▶ Robust metal case to minimize interference
- ▶ Optional rack mounting

Bosch offers a range of high performance monitors which reflects the high standards of other associated units in the Bosch CCTV system, such as cameras, transmission and control equipment. Included in this range of Bosch units are the LTC 2009, LTC 2012 and LTC 2017 Series of monochrome monitors. These monitors offer high performance pictures with a resolution of 900 TVL, or in the case of the LTC 2017 monitor 700 TVL, making them ideal for remote observation and video applications.

Functions

The monitor housing consists of a robust rectangular metal case which minimizes interference from external signals and allows “stacking” of monitors when used in large numbers.

Designed for ease of installation and operation, the monitors will accept a voltage supply of 100-230 VAC, without the need for any switching or adjustments. The monitors are setup for standard composite video signals, the LTC -/5x versions CCIR format and the LTC -/6x versions EIA format.

All controls are located on the front panel for easy adjustment of the picture image. Monitor features include loop through connection; electrical circuits provide safe guards against interference, noise and

changing signal strengths to maintain a clear and stable picture.

Additional features of the LTC 2017 monitors include switchable scanning size (over scan and under scan) and switchable DC restoration. An optional rack mounting is available for these monitors.

Certifications and Approvals

Electromagnetic Compatibility (EMC) Requirements Immunity EN50082-1 1992, Emission EN50081-1 1992, FCC Part 15, Class B

Safety (LTC 2009, LTC 2012, LTC 2017) UL, UL 1410, CE, cUL, EN60065, CSA 22.2#01

Product complies with DHHS Rules 21 CFR applicable at the date of manufacture.

Technical Specifications

Electrical

Model No.	Rated Voltage	Voltage Range	Power at Rated Voltage	Sync Format
LTC 2009/51	230 VAC, 50 Hz	198 to 264	18 W	CCIR
LTC 2009/61	120 VAC, 60 Hz	108 to 132	18 W	EIA
LTC 2012/51	230 VAC, 50 Hz	198 to 264	18 W	CCIR
LTC 2012/61	120 VAC, 60 Hz	108 to 132	18 W	EIA
LTC 2017/50	230 VAC, 50 Hz	198 to 264	27 W	CCIR
LTC 2017/60	120 VAC, 60 Hz	108 to 132	27 W	EIA

Monochrome System

CCIR/EIA, selectable on LTC 2009, LTC 2012, LTC 2017

Video Input

Composite video: 0.5 to 2.0 Vp-p, sync negative. Auto switching from 75 Ohm unbalanced termination to Hi-Z with looped through operation.

Controls

LTC 2009 and LTC 2012: Power, Contrast, Brightness, V-Hold, H-Hold, EIA/CCIR switch, V-Height, V-Lin

LTC 2017: Power, Contrast, Brightness, V-Hold, H-Hold, Under/Over Scan, DC-Restoration, V-Height, V-Lin

Connectors

LTC 2009 and LTC 2012 Power input socket, 2 BNC Video input

LT 2017 Power input lead, 2 BNC Video input

Power Cord

Approx. 1.8 m (6 ft) with a European/Continental plug type

2.4 m (8 ft) with a U.S. plug type

Mechanical

Cabinet

Material: Steel with plastic front; Finish: Charcoal

Dimensions (H x W x D)

LTC 2009 234 x 220 x 248 mm (9.2 x 8.7 x 9.6 in.)

LTC 2012 287 x 305 x 306 mm (11.3 x 12 x 12 in.)

LTC 2017 386 x 419 x 381 mm (15.2 x 16.5 x 15 in.)

Weight

LTC 2009 4.3 kg (9.5 lb)

LTC 2012 8.9 kg (19.6 lb)

LTC 2017 15 kg (33 lb)

Display Tube

Measured diagonally, -90° deflection angle

LTC 2009 23 cm (9 in.)

LTC 2012 30 cm (12 in.)

LTC 2017 43 cm (17 in.)

Viewable Picture Area

LTC 2009 22 cm (9 in.)

LTC 2012 29 cm (11 in.)

LTC 2017 41 cm (16 in.)

Linearity

Horizontal 10% max.

Vertical 10% max.

Horizontal Resolution

LTC 2009, LTC 2012 800 TVL

LTC 2017 800 TVL

Environmental

Operation Temp. -10°C to 50°C (14°F to 122°F)

Storage Temp. -10°C to 50°C (14°F to 122°F)

Humidity Operating: 30 to 90% non-condensing

Ordering Information

LTC 2009/51 Monochrome Monitor 896020095101
23, 30 and 43 cm (9, 12 and 17 in.) models, EIA/CCIR, 700-900 TVL with audio, 120/230 VAC, 50/60 Hz
23 cm (9 in.), B/W CCIR, 900 TVL, 230 VAC, 50 Hz

LTC 2009/61 Monochrome Monitor 896020096101
23, 30 and 43 cm (9, 12 and 17 in.) models, EIA/CCIR, 700-900 TVL with audio, 120/230 VAC, 50/60 Hz
23 cm (9 in.), B/W EIA, 900 TVL, 120 VAC, 60 Hz

LTC 2012/51 Monochrome Monitor 896020125101
23, 30 and 43 cm (9, 12 and 17 in.) models, EIA/CCIR, 700-900 TVL with audio, 120/230 VAC, 50/60 Hz
30 cm (12 in.), B/W CCIR, 900 TVL, 230 VAC, 50 Hz

LTC 2012/61 Monochrome Monitor 896020126101
23, 30 and 43 cm (9, 12 and 17 in.) models, EIA/CCIR, 700-900 TVL with audio, 120/230 VAC, 50/60 Hz
30 cm (12 in.), B/W EIA, 800 TVL, 120 VAC, 60 Hz

LTC 2017/50 Monochrome Monitor 896020175001
23, 30 and 43 cm (9, 12 and 17 in.) models, EIA/CCIR, 700-900 TVL with audio, 120/230 VAC, 50/60 Hz
43 cm (17 in.), CCIR, 700 TVL, 230 VAC, 50 Hz

LTC 2017/60 Monochrome Monitor 896020176001
23, 30 and 43 cm (9, 12 and 17 in.) models, EIA/CCIR, 700-900 TVL with audio, 120/230 VAC, 50/60 Hz
43 cm (17 in.), B/W EIA, 700 TVL, 120 VAC, 60 Hz

Hardware Accessories

LTC 9009/00 Rack Kit 896090090001
for up to two (2) LTC 2009, 26.67 cm (10.5 in.) high

Ordering Information

LTC 9012/00 Rack Kit for one (1) LTC 2012, 31.12 cm (12.25 in.) high	896090120001
LTC 9017/00 Rack Kit for one (1) LTC 2017, 44.45 cm (17.5 in.) high	896090170001

Americas:

Bosch Security Systems
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 585 223 4060
Fax: +1 800 289 0096
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 27 83955
Fax: +31 40 27 86668
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by