

# LTC 9370/00 Indoor Housing



- ► For Fixed or Suspended Ceilings
- Convenient Key Lock Access
- Easy Installation
- ► Attractive Low Profile Styling
- ► Suitable for Use in Environmental Air Spaces
- ► Rotatable Ceiling Tile Mounting Kits Available

The LTC 9370/00 is an aesthetically designed, small, low profile indoor ceiling housing for CCTV camera installations.


This housing can be easily mounted in fixed or suspended ceilings and is ideal for any application where attractive and discreet CCTV monitoring is required.

The LTC 9370/00 construction consists of a tough acrylic/PVC alloy plastic cover hinged to an aluminized steel backbox.

This construction allows the LTC 9370/00 to be used in environmental air spaces or in air handling plenum of a non fire-resistant ceiling. Other construction features include key lock access, a polycarbonate window, an adjustable camera mount system, and cable entry through conduit knockouts.

Optional Mounting kits are available for 2 ft  $\times$  2 ft and 600 mm  $\times$  600 mm suspended ceiling tiles. These mounting kits allow 360° rotation and easy installation.

# **Installation/Configuration Notes**



# **Parts Included**

# Quantity Component

1 LTC 9370/00 Indoor Housing

# **Technical Specifications**

# Mechanical

Maximum Camera/Lens Size	Accepts camera/lens combinations up to 208.3 L x 69.8 W x 63.5 H mm (8.2 x2.75 x2.5 inch).			
Cable Entry	Wiring access available through four (two front and two back) PG13.5 (1/2 inch) conduit knockouts.			
Window	3.2 mm (0.13 inch) thick polycarbonate.			
Housing Mounting	Eight protected 7 mm (0.27 inch) holes in backbox. Top of backbox contains two 6 mm (0.25in) knockouts for safety cable wiring.			
Camera Mounting	Two piece adjustable mounting system.			
Construction/Finish				
Cover	1.6 mm (0.06 inch) acrylic / PVC alloy plastic with a haircell texture and light gray color.			
Backbox	1 mm (0.04 inch) aluminized steel.			
Dimensions	See Dimensional Outline.			
Weight	2.4 kg (5.3 lb).			
Environmental				
Enclosure Protection	Cover and window meet UL Flame Rating 94V-0.			
Accessories				
Mounting Kits	Ceiling tile mounting kits for suspended ceiling installations. Constructed of $1\ \text{mm}$ (0.04 inch) aluminized steel painted with light gray powder coat. Rotates through 360°.			
LTC 9070/00	Replaces a 2 ft x2 ft ceiling tile.			
LTC 9070/01	Replaces a 600 mm x 600 mm ceiling tile.			

Orc	lering	Inf	orma	tion
• • •				

3	
LTC 9370/00 Indoor Housing drop ceiling mount, tamper resistant, camera/lens up to 200 mm (8 inch)	LTC9370/00
Accessories	
LTC 9070/00 Mounting Plate 600 mm x 600 mm (2 ft x 2 ft), for LTC 9370/00	LTC9070/00
LTC 9070/01 Mounting Plate 600 mm x 600 mm (2 ft x 2 ft), for LTC	LTC9070/01

9370/00

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com