

# DINION IP bullet 5000

www.boschsecurity.com



**BOSCH**  
Invented for life



**HD ONVIF**



- ▶ Outdoor IP bullet camera with varifocal lens
- ▶ Built-in IR illuminator with 25 m (82 ft) viewing distance
- ▶ 1080p resolution
- ▶ Fully configurable quad streaming
- ▶ Regions of interest and E-PTZ

The HD 1080p infrared bullet from Bosch is a professional surveillance camera that provides high quality HD images for demanding security and surveillance network requirements.

This robust bullet camera is a true day/night camera offering excellent performance day or night.

## System overview

### Intelligent Dynamic Noise Reduction reduces bandwidth and storage requirements

The camera uses Intelligent Dynamic Noise Reduction which actively analyzes the contents of a scene and reduces noise artifacts accordingly.

The low-noise image and the efficient H.264 compression technology provide clear images while reducing bandwidth and storage by up to 50% compared to other H.264 cameras. This results in reduced-bandwidth streams that still retain a high image quality and smooth motion. The camera provides the most usable image possible by cleverly optimizing the detail-to-bandwidth ratio.

The average typical optimized bandwidth in kbits/s for various image rates is shown in the table:

| IPS | 1080p | 720p | 480p |
|-----|-------|------|------|
| 30  | 1600  | 1200 | 600  |
| 15  | 1274  | 955  | 478  |

|   |     |     |     |
|---|-----|-----|-----|
| 5 | 757 | 568 | 284 |
| 2 | 326 | 245 | 122 |

### Area-based encoding

Area-based encoding is another feature which reduces bandwidth. Compression parameters for up to eight user-definable regions can be set. This allows uninteresting regions to be highly compressed, leaving more bandwidth for important parts of the scene.

### Built-in IR illuminator

The built-in infrared LEDs provides quality night time monitoring with 25 m (82 ft) viewing distance in darkness.

### Outdoor bullet camera with varifocal lens

The robust aluminum housing provides high installation flexibility. The camera resists both water and dust ingress in tough environments and is rated to IP66 (NEMA Type 4X) standards. The 3 to 10 mm varifocal lens allows you to choose the coverage area to best suit your application.

### 1080p resolution with multiple streams

The camera has a resolution of 1080p at 30 images per second (ips). The innovative multi-streaming feature delivers various H.264 streams together with an

M-JPEG stream. These streams facilitate bandwidth-efficient viewing and recording as well as integration with third-party video management systems.

### Regions of interest and E-PTZ

Regions of Interest (ROI) can be user defined. The remote E-PTZ (Electronic Pan, Tilt and Zoom) controls allow you to select specific areas of the parent image. These regions produce separate streams for remote viewing and recording. These streams, together with the main stream, allow the operator to separately monitor the most interesting part of a scene while still retaining situational awareness.

### Two-way audio and audio alarm

Two-way audio allows the operator to communicate with visitors or intruders via an external audio line input and output. Audio detection can be used to generate an alarm if needed.

### Tamper and motion detection

A wide range of configuration options is available for alarms signaling camera tampering. A built-in algorithm for detecting movement in the video can also be used for alarm signaling.

### Cloud-based facilities

The camera supports time-based or alarm-based JPEG posting to four different accounts. These accounts can address FTP servers or cloud-based storage facilities (for example, Dropbox). Video clips or JPEG images can also be exported to these accounts. Alarms can be set up to trigger an e-mail or SMS notification so you are always aware of abnormal events.

### Easy installation

Power for the camera can be supplied via a Power-over-Ethernet (IEEE 802.3af) compliant network cable connection. With this configuration, only a single cable connection is required to view, power, and control the camera. Using PoE makes installation easier and more cost-effective, as cameras do not require a local power source.

The camera can also be supplied with power from +12 VDC power supplies. To increase system reliability, the camera can be simultaneously connected to both PoE and +12 VDC supplies. Additionally, uninterruptible power supplies (UPS) can be used, which will allow continuous operation, even during a power failure. For trouble free network cabling, the cameras support Auto-MDIX.

### True day/night switching

The camera incorporates mechanical filter technology for vivid daytime color and exceptional night-time imaging while maintaining sharp focus under all lighting conditions.

### Access Security

Password protection with three levels and 802.1x authentication is supported. To secure Web browser access, use HTTPS with a SSL certificate stored in the

camera. The video and audio communication channels can be independently AES encrypted with 128-bit keys by installing the optional encryption site license.

### Surveillance software

There are many ways to access the camera's video features: using a web browser, with the Bosch Video Management System, with the Bosch Recording System, with the supplied Bosch Video Client, or with the video security mobile App. The Bosch Video Client PC surveillance software offers a user-friendly interface to support easy installation and configuration, and is supplied completely free-of-charge. It provides easy live viewing of multiple cameras, playback, forensic search and export.

### Video security App

The Bosch video security mobile App has been developed to enable **Anywhere** access to HD surveillance images allowing you to view live images from any location. The App is designed to give you complete control of all your cameras, from panning and tilting to zoom and focus functions. It's like taking your control room with you. This App, together with the separately available Bosch transcoder, will allow you to fully utilize our dynamic transcoding features so you can play back images even over low-bandwidth connections.

### System integration

Bosch IP standard definition and high definition cameras, encoders and analytics work seamlessly with a wide range of security software and recording solutions from Bosch and other industry providers. Through ONVIF conformance, the open availability of Bosch video software development kits and a team dedicated to special integration and support projects, it is easy to manage Bosch video products within your system design (for details on the Bosch Integration Partner Program, visit [ipp.boschsecurity.com](http://ipp.boschsecurity.com)).

## Functions

### Certifications and approvals

#### HD standards

Complies with the SMPTE 274M-2008 Standard in:

- Resolution: 1920x1080
- Scan: Progressive
- Color representation: complies with ITU-R BT.709
- Aspect ratio: 16:9
- Frame rate: 25 and 30 frames/s

Complies with the 296M-2001 Standard in:

- Resolution: 1280x720
- Scan: Progressive
- Color representation: complies with ITU-R BT.709
- Aspect ratio: 16:9
- Frame rate: 25 and 30 frames/s

| Standards | IEC 62471 (IR version) |
|-----------|------------------------|
|           | EN 60950-1             |

|                               |                                     |
|-------------------------------|-------------------------------------|
|                               | UL 60950-1                          |
|                               | CAN/CSA-C22.2 NO. 60950-1-03        |
|                               | EN 50130-4                          |
|                               | EN 50130-5                          |
|                               | FCC Part15 Subpart B, Class B       |
|                               | EMC directive 2004/108/EC           |
|                               | EN 55022 class B                    |
|                               | EN 61000-3-2                        |
|                               | EN 61000-3-3                        |
|                               | EN 55024                            |
|                               | AS/NZS CISPR 22 (equal to CISPR 22) |
|                               | ICES-003 Class B                    |
|                               | VCCI J55022 V2/V3                   |
|                               | EN 50121-4                          |
| <b>ONVIF compliance</b>       | EN 50132-5-2; IEC 62676-2-3         |
| <b>Product certifications</b> | CE, FCC, UL, cUL, C-tick, CB, VCCI  |
| Ingress protection            | IP66                                |
| Impact protection             | IK08                                |
| <b>Region</b>                 | <b>Certification</b>                |
| Europe                        | CE                                  |
| USA                           | UL                                  |

### Installation/configuration notes

### Parts included

### Technical specifications

|  |   |
|--|---|
| <b>Power</b>   |   |
| Input voltage  | +12 VDC or Power-over-Ethernet (48 VDC nominal)       |
| Power consumption                                    | 9.2 W max.  |
| PoE  | IEEE 802.3af (802.3at Type 1)<br>Power level: Class 3 |
| <b>Sensor</b>  |   |
| Sensor type  | 1/2.7-inch CMOS                                       |
| Total sensor pixels                                  | 1952 x 1092 (2MP)                                     |
| <b>Video performance</b>                             |   |
| Sensitivity – (3200K, reflectivity 89%, F1.3, 30IRE) |   |
| • Color  | 0.24 lx   |

|                          |   |
|--------------------------|---|
| <b>Video performance</b> |   |
| • Mono                   | 0.05 lx   |
| • With IR                | 0.0 lx  |
| Dynamic range            | 76 dB Wide Dynamic Range (WDR)  |
| <b>Video streaming</b>   |   |
| Video compression        | H.264 (MP); M- JPEG   |
| Streaming                | Multiple configurable streams in H.264 and M-JPEG, configurable frame rate and bandwidth. Regions of Interest (ROI) |
| Overall IP Delay         | Min. 120 ms, Max. 340 ms  |
| GOP structure            | IP, IBP, IBBP   |
| Encoding interval        | 1 to 25 [30] ips  |

|                                 |  |
|---------------------------------|--|
| <b>Video resolution (H x V)</b> |  |
| • 1080p HD                      | 1920 X 1080                                  |
| • 720p HD                       | 1280 x 720                                   |
| • D1 4:3 (cropped)              | 704 x 480                                    |
| • SD upright (cropped)          | 400 x 720                                    |
| • 480p SD                       | Encoding: 704 x 480;<br>Displayed: 854 x 480 |
| • 432p SD                       | 768 x 432                                    |
| • 288p SD                       | 512 x 288                                    |
| • 240p SD                       | Encoding: 352 x 240;<br>Displayed: 432 x 240 |
| • 144p SD                       | 256 x 144                                    |

|                             |  |
|-----------------------------|--|
| <b>Video functions</b>      |  |
| Day/Night                   | Color, Monochrome, Auto  |
| Adjustable picture settings | Contrast, Saturation, Brightness   |
| White Balance               | 3 automatic modes, manual mode and measure   |
| Shutter                     | Automatic Electronic Shutter (1/25[30] to 1/150000)<br>Fixed shutter (1/25[30] to 1/15000) selectable<br>Default shutter |
| Backlight compensation      | On/off   |
| Noise reduction             | Intelligent Dynamic Noise Reduction with separate temporal and spatial adjustments                                       |
| Contrast enhancement        | On/off   |
| Sharpness                   | Sharpness enhancement level selectable   |

| Video functions          |   |
|--------------------------|---|
| Intelligent defog        | Intelligent Defog automatically adjusts parameters for best picture in foggy or misty scenes (switchable) |
| Privacy Masking          | Four independent areas, fully programmable  |
| Video Analysis           | MOTION+   |
| Other functions          | Image mirror, Image flip, Pixel counter, Video watermarking, Display stamping, Scene modes                |
| Night vision             |   |
| Distance                 | 25 m (82 ft)  |
| LED                      | 12 LED high efficiency array, 850 nm  |
| Lens                     |   |
| Lens type                | Varifocal 3 to 10 mm, DC Iris F1.3 – 360, IR corrected  |
| Lens mount               | Board mounted   |
| Horizontal field of view | 36° - 117°  |
| Vertical field of view   | 20° - 61°   |
| Input/output             |   |
| Analog video output      | CVBS, 1 Vpp, BNC connector, 75 Ohm Selectable standard  |
| Alarm input              | Short or DC 5V activation   |
| Relay out                | Input rating Maximum 1 A, 24 VAC/VDC  |
| Audio input              | Line in jack connector  |
| Audio output             | Line out jack connector   |
| Audio streaming          |   |
| Audio Streaming          | Full duplex / half duplex   |
| Signal-to-noise ratio    | > 50 dB   |
| Audio compression        | AAC-LC, G.711, L16 (live and recording)   |
| Software                 |   |
| Unit Configuration       | Via web browser or Configuration Manager  |
| Firmware update          | Remotely programmable   |
| Software viewer          | Web browser, Bosch Video Client, or third party software  |

**Represented by:**

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

**China:**  
Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

**America Latina:**  
Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com

| Network                               |   |
|---------------------------------------|---|
| Protocols                             | IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, Telnet, ARP, DHCP, NTP (SNTP), SNMP (V1, MIB-II), 802.1x, DNS, DNSv6, DDNS (DynDNS.org, selfHOST.de, no-ip.com), SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox, CHAP, digest authentication |
| Encryption                            | TLS 1.0, SSL, DES, 3DES, AES (optional)   |
| Ethernet                              | 10/100 Base-T, auto-sensing, half/full duplex   |
| Connectivity                          | ONVIF Profile S , Auto-MDIX   |
| Mechanical                            |   |
| 3-axis adjustment (pan/tilt/rotation) | 350° / 100° / 350°  |
| Dimensions (H x W x D)                | 103 x 100 x 252 mm (4.06 x 3.94 x 9.92 in)  |
| Weight                                | 1.6 kg (3.53 lb) approx.  |
| Color                                 | Pantone 877c  |
| Environmental                         |   |
| Operating temperature                 | -30 °C to +50 °C (-22 °F to +122 °F)  |
| Storage temperature                   | -30 °C to +70 °C (-22 °F to +158 °F)  |
| Humidity                              | 20% to 90% relative humidity (non condensing)   |

**Ordering information****DINION IP bullet 5000 HD**

Robust infrared IP bullet camera for demanding HD surveillance. IP66; PoE; day/night function; IDNR; ROI; H.264 quad-streaming; free viewing Apps; cloud services; tamper/motion detection; 1080p  
Order number **NTI-50022-V3**

**Software Options****BVIP AES 128 Bit Encryption**

Site licence for BVIP AES 128-bit encryption. Enables encrypted communication between BVIP devices and management stations  
Order number **MVS-FENC-AES**