



## General Specifications

<b>Power Requirement</b>	- VDC regulated	7-16 VDC
<b>Current Consumption</b>	- Average	45ma
	- Peak	135ma
<b>Card Read Range</b>	- Metric	20mm - 40 mm
<b>Operating Temperature</b>	- USA	0.8" - 1.6"
	- Metric	-25°C to +65°C
<b>Relative Humidity</b>	- USA	-13°F to +149°F
	- % max	90%, operating non condensing
<b>Reader Dimensions</b>	- Metric	110mm (L) x 110mm (W) x 23mm (D)
	- USA	4.33" (L) x 4.33" (W) x 0.91" (D)
<b>Status LED's</b>	- Colour	Green and Red
<b>Audible Tone</b>		Internal & external buzzer control
<b>Colour finish</b>		Charcoal
<b>Certifications</b>		C-tick, FCC, CE
<b>IP Rating</b>		IP65
<b>ROHS</b>		Compliant

M1000

*Security with aesthetics in mind and a stylish flush mount design*

The BT815F Series of readers is a flush mount unit designed to be architecturally unobtrusive. The BT815F offers flexible security options in a low profile design.

Available in several models, the BT815F caters for all security requirements large or small and offers a solution for all applications whether driven by budget or functionality.

## Model Features

BT815F	Technology			Authentication Factors			Encode				Encryption				Sector Keys			13.56MHz Credential type and option				Output Protocol			Other					
	Mifare Classic	Mifare Plus	DESfire	Card	Biometric	Keypad	CSN/UID	Sector	Application	Random UID	Diversified Keys	Crypto 1	Mifare Plus	3 DES	AES (optional)	MiPASS 2	MiPASS 3	Customisable	ISO14443A	ISO14443B	Mifare 1K & 4K	Mifare Plus 2K & 4K	DESfire EV1 4K & 8K	Wiegand 32 BIT	Wiegand 26-199 BIT	Encrypted RS485*	Read / Write	Indoor / Outdoor	Tamper option	
BT815F-2	✓			✓			✓	✓		✓	✓				✓				✓	✓				✓			✓	✓		
BT815F-3	✓			✓			✓	✓		✓	✓						✓	✓	✓	✓				✓	✓	✓	✓	✓	✓	✓
BT815F-4		✓	✓				✓	✓	✓	✓	✓		✓			✓			✓	✓			✓	✓			✓	✓		
BT815F-6	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

\* Requires High Security Module (HSM) AES 128bit encryption