
CAPTURE

FEATURES:

- Versatile display formats provide a convenient user interface.
- Full-screen with 2xZoom, 2x2,
 Picture-in-Picture (PIP) display
- Cameras can be assigned to any picture format
- Dual monitor outputs (MAIN and SPOT) allow simultaneous multi-camera and full-screen viewing
- "Dynamic Scene Sensing" motion detection
- On-screen display includes date, time, alarm status, video loss and camera titles
- Capable of live, VCR or preview mode during recording
- User-friendly programmable menus
- Camera alarm input is activated by contact closure or TTL/CMOS signal
- Alarm input polarity is selectable
- Rack mountable (brackets included)
- Control multiple units from 1 keyboard via
 RS-485 (keyboard optional)
- Individual dwell settings
- 3 Year Warranty









Distributed by:



1-800-722-CCTV

Please contact your local representative for additional information.



4-Channel Duplex Color Multiplexer















Specifications:

Video Input	1 Vp-p, 75 Ohm Camera input: 4 EA (BNC)
Video Output	1 Vp-p, 75 Ohm Looping output: 4 EA (BNC) SPOT output: 1 EA (BNC) MAIN output: 1 EA (BNC or Y/C) High Resolution: 720x480 pixels with 256 level gray scale
VCR In/Out	1 Vp-p, 75 Ohm, 1 EA BNC or Y/C
Alarm	DB-25S Female Alarm input: 4 EA Alarm output: 1 EA (NC/NO/COMMON) Alarm hold time: 0-99 sec.; default: 20 sec.
Input power	12VDC, 1.5A
Ambient Temperature	32°F to 95°F 0°C to 35°C
Ambient Humidity	10% to 90% (non-condensing)
Dimensions W x H x D	17 x 1.75 x 12.25 (in) 432 x 44 x 310 (mm)
Net Weight	6.2 lbs 2.8 kg



1-800-471-2003

CPT0101