CAPTURE

FEATURES:

- Universal power supply
- EIA/CCIR auto-selection system
- Auto termination selectable
- DC restoration on/off selectable
- Under/over scan selectable
- Removable power cord
- 3 Year Warranty



CPT-MM20U

20" Black & White Monitor with Audio



Distributed by:



1-800-722-CCTV

Please contact your local representative for additional information.













Specifications:

Picture Tube	20" Diagonal 90° Deflection Angle
System	EIA-CCIR Standard
Resolution	900 TVL (Center)
Input Signal	1.0V p-p (75 Ohm)
SCANNING	
Horizontal	EIA: 15.734KHz CCIR: 15.62KHz
Vertical	EIA: 59.94KHz CCIR: 50KHz
LINEARITY	
Horizontal	10% max
Vertical	10% max
ACTIVE DISPLAY AREA	
Horizontal	10% overscanning
Vertical	13% overscanning
Connectors	A/B Input/Output
Front Controls	H-Size, V-Size, H-Hold, V-Hold, Brightness, Contrast, Sharpness, Volume, Scan Switch, (Under/Over) A/B Selector, Power
Back Controls	DC Restoration, Vertical Linearity
Power Source	120-240VAC, 50/60Hz
Consumption	40 Watts
Operating Temperature	0°C - 40°C 32°F - 104°F
Ambient Humidity	10% to 90%
Dimensions W x D x H	445mm x 441mm x 380mm 17.52in x 17.36in x 14.96in
Weight	39.7 lbs 18.0 kg
Audio Input	300 Vrms 1 Watt

TECHNICAL SPECIFICATION

www.capturecctv.com (CAPTURE)

1-800-471-2003

CPT0101