CAPTURE

FEATURES:

- Real time refresh
- Quad picture display
- Still picture display in QUAD mode
- Auto Freeze when video loss in QUAD mode
- One camera per selected mode full screen capability
- Automatic sequential switching with Quad picture
- Automatic skip when video loss
- Four looping video output capability for external video device
- Variable dwell time (0-60 seconds)
- VIS (Vertical Interval Switching) capability
- Rack mountable (brackets included)
- 4 alarm inputs
- Variable alarm hold time (4-60 seconds)
- Alarm output can trigger VCR alarm mode or an external device
- On-screen display (RS-485, RS-232, dry contact)
- All user-programmed data is battery backed
- 3 Year Warranty





Distributed by:



1-800-722-CCTV

Please contact your local representative for additional information.



MONOCHROME OUAD















Specifications:

Video Input	1 Vp-p, 75 Ohm Camera input: 4 EA (BNC)
Video Output	1 Vp-p, 75 Ohm Looping output: 4 EA (BNC) CALL output: 1 EA (BNC) QUAD output: 1 EA (BNC) High Resolution: 512x480 pixels with 256 level gray scale
Alarm	Alarm input: 4 EA Alarm output: 1 EA (NC/NO/COMMON) Alarm hold time: 4-60 sec. variable
Bell	On/Off switch
Input power	12VDC, 1A adaptor (included)
Ambient Temperature	32°F to 95°F 0°C to 35°C
Ambient Humidity	10% to 90% (non-condensing)
Power Comsumption	Max. 5W
Dimensions W x H x D	17 x 1.75 x 12.25 (in) 432 x 44 x 310 (mm)
Net Weight	6.2 lbs 2.8 kg

www.capturecctv.com (CAP)



1-800-471-2003

CPT0101