Video Entry, 1-Way
Standard & Vandal Resistant

* Standard or Vandal Resistant
* Easy 2 or 4 Wire System
* Up to 2 Monitors - 2 Wire
* Up to 4 Monitors - 4 Wire
* Up to 2 Door Stations - 4 Wire
* "Hands-Free" - 2 Wire
* Integral Keypad/Prox Option
* New Colour Option - 4 Wire

2-Wire Monitor "Hands-Free"

Standard Surface Camera

Stainless Surface Camera

4-Wire Monitor

New CDV-50 Colour LCD Monitor - 5" TFT

For long cable runs, please be aware of volt drop - if in doubt, please call our sales office

Kit includes:
1 x Door Entrance Camera Unit
1 x Monitor
1 x 240vac Adaptor

Note

Product Code

SVE-F-2	1-Way Kit, 2-Wire, Flush
SVE-S-2	1-Way Kit, 2-Wire, Surface
VRVE-F-2	1-Way Kit, 2-Wire, Stainless, Flush
VRVE-S-2	1-Way Kit, 2-Wire, Stainless, Surface
DPV-2KH	Additional Monitor for 2-Wire
SVE-F-4	1-Way Kit, 4-Wire, Flush
SVE-S-4	1-Way Kit, 4-Wire, Surface
VRVE-F-4	1-Way Kit, 4-Wire, Stainless, Flush
VRVE-S-4	1-Way Kit, 4-Wire, Stainless, Surface
DPV-4MT	Additional Monitor for 4-Wire
DP-4VR	Audio Handset for 4-Wire
DRC-40BS	Additional Door Station, 4-Wire
VRVE-40BS	Additional Stainless Door Station, 4-Wire
SVE-F-4-C	1-Way Kit, 4-Wire, Flush, Colour
SVE-S-4-C	1-Way Kit, 4-Wire, Surface, Colour
VRVE-F-4-C	1-Way Kit, 4-Wire, Stainless, Flush, Colour
VRVE-S-4-C	1-Way Kit, 4-Wire, Stainless, Surface, Colour
CDV-50	Additional Monitor for 4-Wire Colour
VRVE-CAS	Integral Keypad, 50 Codes
VRVE-PROX	Integral Proximity Reader, 500 Users
ENG-1	Special Engraving

Specification

Input Voltage:	240vac, to supplied adaptor
Power:	3W
CCD Camera Mono:	1/3", 0.1 Lux, 380 Lines
CCD Camera Colour:	1/3", 1.0 Lux, 380 Lines
Monitor Mono:	4" Flat Tube, 380 Lines, Wall Mount
Monitor Colour:	5" LCD, TFT
Operating Temp:	Door Station, -25 to +50C
Finish, Door Station:	Cast Aluminium
	Stainless Steel on Vandal Resistant

For more specific information, please contact our sales department

Making your security a permanent asset...