




# **Underground Gate Operator**



**Gate Support with Ball-Bearing** 








the luxury class: the underground motor - for the sophisticated look

Under the gate, set in secrecy, for those who put high demands on an opener.

#### Features:

- Maintenance free
- Serviceability without removing the wing
- Permanent Lubrication
- Mechanical System
- Water-proof motor
- Stabile electronic box with control plate
- Additional gate support with ball bearings
- High performance for heavy gates
- Manual release in the gate arm connector

#### two-year warranty



### **Ordering Assistance for Kits**

- ♦ UGO300B Box
- ♦ UGO300M Motor
- ♦ Electronic Control GOC1A (recommended)
  - Radio Module & Adapter 801719
  - Remote Control 433MHz (refer to "Accessories")
  - Antenna ANT4X-1LM
  - Safety Module (801696) for Operation with Infrared Sensor
- ♦ Flashing Light FLA230-2
- ♦ Infrared Sensor 100263
- ♦ Key Switch 100027





Install all equipment in compliance with EN60335-2-103

#### OPTIONAL ACCESSORIES:

- 600091 Main Switch
- 600008 IR Stand
- 600084 Emergency Stop
- **600046** Safety Edge

## **Specification Chart**

		UGO300M
Voltage In	V AC	230
Frequency	Hz	50
Power	W	190
Current	А	1.3
Rated Thrust	N	380
Capacitor	microF	10
Thermal Overload Protection	deg C	135°
Motor Speed	RPM	1400
Duty Cycle (max)	cycles/hr	20
Working Temperature Range	deg C	-35°C to 80°C
Protection Class		I
Degree of Protection	IP	57
Weight (motor)	kg	10
Electronic Controls		no
Remote Controls		no
Frequency	MHz	N/A
IR Sensor		no
Flashing Light		no
Key Switch		no
Antenna Kit		no
Max Gate Wing Length	m	3
Max Gate Wing Weight at max. Wing Length	kg	300kg

- 600015 Key Switch Stand
- 100263 Extra Infrared Sensors
- 4330E/4332E/4333E/4335E Remote Controls
- 747E Wireless Keyless Entry