

PCU-5 Pull Cord Unit Series

One Pull Can Be Life-Saving



Wireless Pull Cord Unit PCU-5 Series can be easily installed anywhere in the home for the user to pull for emergency help. When pulled, the PCU-5 will immediately trigger an alarm, which will be sent by its connected medical alarm to the monitoring center or care personnel.

The wall-mounted or ceiling-mounted PCU-5 can be life-saving when the user does not wear a personal trigger. Ideal for bedrooms, bathrooms or kitchen, PCU-5 strategically placed around the home will add an extra level of safety and reassurance in case of an emergency. PCU-5 requires very low maintenance and low battery consumption, with automatic low battery reporting and 24-hour supervision features to prevent operational irregularities and strengthen protection for the user. The PCU-5 is a simple, easy to install, wireless option for raising an alarm.

The PCU-5 F1 models, which adopt Climax's cutting-edge F1 technology to deliver extensive RF communication range, can be flexibly deployed across large or complex premises. Compatible with Climax's F1 control panels, the PCU-5-F1 also features fast signal transmission and an even longer battery life.

Features

- Raise an alarm by pulling the attached cord
- Wireless for easy installation or relocation
- Wall-mount or Ceiling-mount indoor installation
- Extensive RF communication range & faster signal transmission (PCU-5-F1 only)
- IPX4 Waterproof standard
- Low battery detection
- Supervision signals to check system integrity
- Strategic positioning around the home provides extra level of safety

Specifications

PCU-5-F1

Frequency	868 MHz / 433 MHz
Power Source	3V, CR2 Lithium battery x1
Battery Life	10 years*
Waterproof Level	IPX4
Cord Length	175mm
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	81mm x 82mm x 44mm

* Note: Actual battery life may vary with product settings, operating environment and usage.

PCU-5 Pull Cord Unit Series

Specifications

PCU-5

Frequency	868 MHz / 433 MHz
Power Source	3V, CR2 Lithium battery x1
Battery Life	5 years*
Waterproof Level	IPX4
Cord Length	175mm
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	81mm x 82mm x 44mm

* Note: Actual battery life may vary with product settings, operating environment and usage.

Ordering Information

- PCU-5-F1** Pull Cord Unit, compatible with Climax's F1 Control Panel and extensive RF range
- PCU-5** Pull Cord Unit, compatible with Climax's Control Panel and gateways