



The ComNet™ CNGE24MS has eight 100/1000Base-FX SFP ports and sixteen Gigabit combo ports that allow for TX or FX transmission. All SFP ports utilize ComNet SFP* modules for fiber and connector type and distance. The IEEE802.3-compliant unit offers multiple Ethernet redundancy protocols (ComRing, C-Ring, and MSTP/RSTP/STP) which protect your applications from network interruptions or temporary malfunctions by redirecting transmission within the network. The switch provides advanced IP-based management that can limit the maximum bandwidth for each connected IP device, allowing the user to adjust usage. Application-based QoS can set a higher priority for data streaming. The Device-Binding function can prevent unauthorized network access, increasing security. The unit also provides advanced DOS/DDOS auto prevention. If IP flow becomes too large, too quickly, the switch will lock the source IP address for a set period preventing unauthorized access. The switch offers centralized and convenient management and is also configurable by Web-based Telnet, and Console (CLI) configurations.

FEATURES

- › 24 Gbps Ports: 8 × 100/1000Base-FX SFP Ports
16 × Gigabit Combo Ports
- › Fast Redundancy/Recovery; ComRing (recovery time <30ms over 250 units of connection) and MSTP/RSTP/STP (IEEE 802.1s/w/D)
- › Supports IPV6 new internet protocol version
- › Provided HTTPS/SSH protocol enhances network security
- › Supports SMTP client
- › Supports IP-based bandwidth management
- › Supports application-based QoS management
- › Supports Device Binding security function
- › Supports DOS/DDOS auto prevention
- › IGMP v2/v3 (IGMP snooping support) for filtering multicast traffic
- › Internal Power Supply
- › Supports SNMP v1/v2c/v3 & RMON & 802.1Q VLAN Network Management
- › Supports ACL, 802.1x User Authentication for security
- › Supports 9K Bytes Jumbo Frame
- › Multiple notifications warn of unexpected events
- › Web-based, Telnet, Console (CLI), and Windows-based utility (eConsole) configuration
- › Supports LLDP Protocol
- › 19 inch rack mountable design
- › Lifetime Warranty

* Small Form-Factor Pluggable Module. Sold separately.

SOFTWARE SPECIFICATIONS

Network Redundancy	ComRing C-Ring) Fast Recovery Mode STP RSTP MSTP
MAC Table	8K MAC Addresses
Jumbo Frame Switch Properties	Up to 9K Bytes Switching latency: 7µs Switching bandwidth: 48Gbps Max. Number of Available VLANs: 256 IGMP multicast groups: 128 for each VLAN Port rate limiting: User Define Store-and-Forward
Processing	
Priority Queues	4
Security Features	Device Binding security feature Enable/disable ports, MAC based port security Port based network access control (802.1x) VLAN (802.1Q) to segregate and secure network traffic RADIUS centralized password management SNMPv3 encrypted authentication and access security Https / SSH enhance network security
Software Features	STP/RSTP/MSTP (IEEE 802.1D/w/s) Redundant Ring (C-Ring) with recovery time less than 30ms over 250 units Com-Ring supporting proprietary manufacturer redundancy features TOS/Diffserv supported Quality of Service (802.1p) for real-time traffic VLAN (802.1Q) with VLAN tagging and GVRP supported IGMP Snooping IP-based bandwidth management Application-based QoS management DOS/DDOS auto prevention Port configuration, status, statistics, monitoring, security DHCP Client/Server SMTP Client
Ethernet Standards	IEEE 802.3 for 10Base-T IEEE 802.3u for 100Base-TX and 100Base-FX IEEE 802.3ab for 1000Base-T IEEE 802.z for 1000Base-X IEEE 802.3x for Flow control IEEE 802.3ad for LACP (Link Aggregation Control Protocol) IEEE 802.1p for COS (Class of Service) IEEE 802.1Q for VLAN Tagging IEEE 802.1D for STP (Spanning Tree Protocol) IEEE 802.1w for RSTP (Rapid Spanning Tree Protocol) IEEE 802.1s for MSTP (Multiple Spanning Tree Protocol) IEEE 802.1x for Authentication IEEE 802.1AB for LLDP (Link Layer Discovery Protocol)

HARDWARE SPECIFICATIONS

Physical Ports	16 × Gigabit Combo port with 100/1000Base-T(X) and 100/1000Base-X SFP ports 8 × 100/1000Base-X with SFP port
Serial Console Port	RS-232 in DB9 connector with console cable. 115200bps, 8, N, 1
LED indicators	Power Indicators, System Ready, Ring Master, Ring Indicator, Fault Indicator, System Running, Supervisor Login, Reset to Default, Ping Command, 100/1000Base-T(X) RJ45 Port Indicator, 100/1000Base-X SFP Port Indicator
Size (W × D × H)	43.1 × 34.2 × 4.4cm (17 × 13.5 × 1.7 in)
Weight	4.3Kg / 9.5lb
Power	Redundant Input Power: 100~240VAC at AC Input with power cord or 48VDC at 6-Pin Terminal Block Power Consumption (Typ.): 33 Watts Overload Current Protection: Present
Environmental	Storage Temperature: -40 to 85°C (-40 to 185°F) Operating Temperature: -40 to 75°C (-40 to 167°F) Operating Humidity: 5% to 95% Non-condensing MTBF: >100,000 hours Installation: Desktop or 19-inch Rack Mount



Regulatory Compliance

EMI: FCC Part 15, CISPR (EN55022) class A
EMS: EN61000-4-2 (ESD), EN61000-4-3 (RS), EN61000-4-4 (EFT), EN61000-4-5 (Surge), EN61000-4-6 (CS), EN61000-4-8, EN61000-4-11
Shock: IEC60068-2-27
Free Fall: IEC60068-2-32
Vibration: IEC60068-2-6
Safety: EN60950-1

ORDERING INFORMATION

Part Number	Description	100/1000FX Ports	Combo Ports
CNGE24MS	Environmentally Hardened Managed Ethernet Switch	8	16

In a continuing effort to improve and advance technology, product specifications are subject to change without notice.