# PS12DC-HT





### Description

The ComNet<sup>™</sup> PS12DC-HT power transformer supplies 12V DC power to ComNet<sup>™</sup> stand-alone units. The PS12DC-HT operates on 100-240 VAC. The PS12DC-HT is provided for installations with high ambient temperatures.

## Features

- Universal power input, 100-240 VAC
- High temperature operating range
- Lifetime Warranty

### specifications

#### **ELECTRICAL & MECHANICAL**

Power: Input: Output: Size (in./cm) (L×W×H) (excluding line cord)

100-240 VAC, 50-60 Hz @ 0.6 A Max. 12 VDC @ 1.5 A Max.

Shipping Weight:

#### **ENVIRONMENTAL**

MTBF: Operating Temp: Relative Humidity:  $(11.5 \times 4.5 \times 3.1 \text{ cm})$ <0.5 lb./0.25 kg

4.53 × 1.77 × 1.22 in.,

>100,000 hours 0° C to +75° C 20% to 90% (non-condensing)



PART NUMBER	DESCRIPTION
PS12DC-HT-EU PS12DC-HT-UK	12VDC High Temperature PSU



Complies with FDA Performance Standard for Laser Products, Title 21, Code of Federal Regulations, Subchapter J

In a continuing effort to improve and advance technology, product specifications are subject to change without notice.

3 CORPORATE DRIVE | DANBURY, CT 06810 | USA T: 203.796.5300 | F: 203.796.5303 | TECH SUPPORT: 1.888.678.9427 | INFO@COMNET.NET

8 TURNBERRY PARK ROAD | GILDERSOME | MORLEY | LEEDS, UK LS27 7LE T: +44 (0)113 307 6400 | F: +44 (0)113 253 7462 | INFO-EUROPE@COMNET.NET