

IP90

2 Megapixel / HD H.264 / ICR / IR LED / microSD



- Small and smart functional design
- 2 megapixel / HD resolution
- Dual H.264, MPEG-4 or M-JPEG
 video stream
- True Day/Night functionality with built-in IR-cut filter and IR LED
- Two-way audio with built-ir microphone and speaker
- Compatible with ONVIF standard
- Smart motion and audio detection
- microSDHC slot for storing even snapshots and recordings
- Remote surveillance on mobile phone
- Upgradeable for 802.11 b/g/n wireless LAN with USB wireless adapter

Compro IP90 Day/Night network camera offers clear and sharp video quality in all lighting conditions. IP90 with a slew of professional surveillance features is ideal for deployment in homes, offices, shops, etc.

High Quality Megapixel/HD Image

The 2 megapixel/HD resolution IP90 offers lets you view details and identify people and objects at least three times better than on a conventional CCTV camera. The maximum 1600 by 1200 resolution allows IP90 to capture video from a wide area, effectively reducing the number of cameras required in building a reliable video surveillance network.

Smart Motion and Audio Detection

IP90 can detect motion in its field of view, with configurable detection zones and sensitivity. It also supports full-duplex and bi-directional audio communication through a built-in microphone, speaker and audio in/out port, allowing you to eavesdrop on the monitored area and broadcast your voice to intruders. IP90 is also capable of triggering alarms, door lock or other I/O devices when events are detected.

Easy Wireless Network Installation

802.11 b/g/n wireless LAN is supported with a simple and easy wireless installation process.

True Day & Night Functionality for 24/7 Surveillance

IP90 offers Day/Night functionality with its mechanical IR-cut filter, 6 IR LEDs, and a professional-class ambient light sensor, all aimed at providing crystal clear images round-the-clock. The light sensor detects environmental lighting conditions. When in low-light conditions, the 6 built-in IR LEDs are automatically switched on to provide additional infrared light that help deliver clear night-time image.

Total Surveillance Solution for Home and Business

IP90 is bundled with a wealth of applications to provide an intelligent surveillance solution, including iWzard, WebVUer, and ComproView®. iWizard is a smart installer to turn the complicated network camera installation into a simple and fast process. WebVUer is an intuitive IE-based video management software loaded with all the key features for trouble-free remote monitoring. ComproView® is a powerful feature-rich 32-channel professional grade video management software.









	Camera
Image Sensor	1/3" progressive scan CMOS 2 megapixel
Lens	 Focal Length: 4.0 mm Max Aperture Ratio: F1.5 Fixed iris, IR-corrected, adjustable focus
Zoom	10x digital zoom
Angle of View	60° horizontal
Focusing Range	0.5m ~ INF
Minimum Illumination	• IR Mode: 0 lux with built-in IR LEDs on (6 LEDs in total; effective distance up to 8m) • Color Mode: 1.0 lux
Shutter Time	1/5 ~ 1/16000 Sec.
	Video
Video Compression	• H.264 (MPEG-4 Part 10) • Motion JPEG • MPEG-4 Part 2
Resolutions	160x120, 320x240, 640x480, 1280x720, 1280x1024, 1600x1200
Frame Rate	• Up to 30 FPS at 1280 x 720 (720P) • Up to 15 FPS at 1600 x 1200 (UXGA)
Video Streaming	Dual video stream
Image Settings	 Adjustable image size and quality AGC, AWB, AES Configurable brightness, saturation and sharpness
	Audio
Audio Communication	Two-way audio with built-in MIC (S/N ratio 58 dB, 50-10000hz) and speaker (660mv)
Audio compression	G.711 PCM 64Kbit/sec
Audio input / output	MIC input / audio output
	Network
Security	User ID / Password protection
Supported Protocols	TCP/IP, HTTP, UDP, FTP, ICMP, ARP, DHCP, NTP, DDNS, DynDNS, UPnP, RTP, RTSP, RTCP, SMTP, IGMP, 3GPP, IPv4, 802.1x
	Firmware
Firmware	Support UPnP Support online firmware update

Hardware Overview Light Sensor IRLED (inside) Focus Adjuster Connector Lens Adjuster Status LED Speaker Mic In Power Adapter Port Rear Rear

Advanced Video Surveillance **ComproView®** • Multi-channel management (32-channels) • Fast and intuitive camera setup • Search and playback recordings by event types • Scheduled and event-based management • Smart motion and audio detection • Remotely view and configure camera on **Internet Explorer** (ActiveX) Internet Explorer • Record video and capture snapshots on PC; download recordings from microSD card • Alarm and event management: FTP, I/O alarm, server notification, SMS/Email alert **Supported Viewing** • PC, laptop, tablet, nettop, MID with IE8 **Devices** • iPhone/iPad, BlackBerry, Android, WM, PDA, or cell phones with web browser (MJPEG mode) **Smartphone App** View H.264/MPEG-4 video on iPhone/Android phone **MJPEG Mode** View live image on mobile web browser **3GPP Mode** View live video on 3G cell phone (3GPP Streaming) **Operating Condition** 5 °C ~ 40 °C **Power Supply** DC 5V/2A • Computer with 1.7GHz processor and 512 MB System memory or above Requirements · Supported Operating Systems: Windows XP SP3, Vista SP1, Windows 7, Mac OS X 10.6 (viewing only) • IP90 network camera Package **Contents** • Software CD (manual included) Quick installation guide Power adapter • Ethernet cable · Screws for ceiling mounting Screw mount

Optional Accessory

Dimensions



WL155 802.11 b/g/n Wireless USB Adapter

84 x 124.5 x 91.5 mm (including bracket)

- Complies with IEEE 802.11n, IEEE 802.11g, and IEEE 802.11b standard
- High data transfer rate up to 150Mbps
- Supports 64/128-bit WEP, WPA, WPA2 function for high-level security
- Supports USB 2.0/1.1 interface
- Portable and mini-size design



