

H6Z0812

6X 8mm - 48mm F1.2
for 1/2 type Cameras, Manual Zoom
C-Mount


| | | | | | | | | |
|----------------------------|---------------------|-----------------|--------------------|-------------|-----------------|----------|--------------|--------------|
| Model No. | H6Z0812 | | Effective | Front | Ø32.9mm | | | |
| Focal Length | 8mm - 48mm | | Lens Aperture | Rear | Ø16.6mm | | | |
| Max. Aperture Ratio | 1:1.2 | | Back Focal Length | 11.4mm | | | | |
| Max. Image Format | 6.4mm x 4.8mm(Ø8mm) | | Flange Back Length | 17.526mm | | | | |
| Operation Range | Iris | F1.2 - F16C | | Mount | C-Mount | | | |
| | Focus | 1.2m - Inf. | | Filter Size | M49 P=0.75mm | | | |
| | Zoom | 8mm - 48mm | | Dimensions | Ø51.75mm x 97mm | | | |
| Control | Iris | Manual | | Weight | 305g | | | |
| | Focus | Manual | | | | | | |
| | Zoom | Manual | | | | | | |
| Object Dimension at M.O.D. | 8mm | 98.4cm x 72.2cm | | | | | | |
| | 48mm | 16.8cm x 12.8cm | | | | | | |
| Angle of View | D | 1/2 type | 55.8° - 9.9° | 1/3 type | 41.8° - 7.5° | 1/4 type | 31.4° - 5.6° | |
| | H | | 44.6° - 8.0° | | | | 33.5° - 6.1° | 25.2° - 4.6° |
| | V | | 33.5° - 6.1° | | | | 25.2° - 4.6° | 18.9° - 3.4° |
| Operating Temperature | -20°C - +50°C | | | | | | | |

1/2
type

C

M.O.D. : Minimum Object Distance

Dimensions



| | |
|-------------|----------|
| GEAR | |
| DIAMETER | Ø51.75mm |
| GEAR NUMBER | 115 |
| MODULE | 0.45 |