Conway EH Range - EH0, EH1, EH2, EH3, EH4 & EH5

EH Range The environmental housing is one of the cornerstones of many CCTV installations. Accessibility for camera servicing and long term environmental durability are key points to look for.

Now with resized EH0 and EH1 units to give the installer confidence to fit large lenses in a more compact housing.

Manufactured from high quality aluminium alloy all models of external camera housings come complete with heater/de-mister.

Heaters The heater is used where condensation needs to be prevented or the temperature may fall below a minimum value. PTC heating elements are semiconductors which adjust their performance according to the ambient temperature and are available in either 110-250V AC/DC & 12-36V AC/DC – please state when ordering required type.

Camera mounting platforms and cable termination rails are standard plus base stiffener plates for the EH0-EH4. The stiffener plate provides a suitable mounting position for the Conway Omega DC telemetry receiver, Delta AC Receiver, Alpha AC Receiver and wash wipe card.

Options Other available options include fan blown sun-visor, Marine finish (Stainless Steel) and anti-tamper features making the EH range suitable for a multitude of applications.

Wipers The /W integral wiper option is an innovative design that offers the end user a neat compact wiper option and overcomes the problem of external wiper units restricting tilt movement. All housings from EH3 to EH0 have fixing holes as standard to give the option of upgrading with a W1 external wiper at a later date.

Special Finishes At Conway we manufacture all of our products at our factories in High Wycombe and are therefore able to apply special colour finishes to customer specifications.

All Aluminium Construction

Integral Wiper Option

Low or High Voltage Heater/ Demister Options

Laminated Glass Screen

Stainless Steel Clip Fasteners

4" PCD Mounting Point

Can House Conway Telemetry Receivers

Fan Blown Options

Available in Stainless Steel

Anti-Tamper Options

Large Range of Sizes

Safety Chain Between Base and Lid

Kit Bag with Screws, Glands & Insulated Camera Mount

Manufactured to IP65

Standard Finish
BS 10A03 Morning Mist

All Conway Housings are available in Stainless Steel



Conway EH4. Inset picture EH4 W. (Not shown to scale)



EH Range DO1-1 issue 1 – 17/06/99 Page 1 of 2

EH0

Technical Data

Mounting

4" PCD

Window Sizes

170 x 149mm

Glass Sizes

195 x 174 x 6.4mm

Weight

8.5 kg

Power Consumption

6 watts (approx)

EH1

Technical Data

Mounting

4" PCD

Window Sizes

170 x 149mm

Glass Sizes

195 x 174 x 6.4mm

Weight

7 kg

Power Consumption

6 watts (approx)

EH2

Technical Data

Mounting

4" PCD

Window Sizes

170 x 105mm

Glass Sizes

195 x 130 x 6.4mm

Weight

5 kg

Power Consumption

6 watts (approx)