

## DH-DVR2104C-H

---

### 4 Channel 960H Smart 1U Home-use Standalone DVR



### Features

- > Up to 4 cameras with 1080p realtime preview
- > H.264 dual-stream video compression
- > DVR2104C-H: All channel 960H realtime recording
- > HDMI/VGA simultaneous video output
- > 4 channel synchronous realtime playback, GRID interface & smart search
- > Support 1 SATA HDD up to 4TB, 2 USB2.0
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

# DH-DVR2104C-H


## Technical Specifications

<b>Model</b>	<b>DH-DVR2104C-H</b>	
<b>System</b>		
Main Processor	Embedded processor	
Operating System	Embedded LINUX	
<b>Video</b>		
Input	4 channel, BNC	
Standard	NTSC(525Line, 60f/s), PAL(625Line, 50f/s)	
<b>Display</b>		
Interface	1 HDMI, 1 VGA,	
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768	
Display Split	1/4	
Privacy Masking	4 rectangular zones (each camera)	
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording	
<b>Recording</b>		
Video/Audio Compression	H.264 / G.711	
Resolution	960H(960×576/960×480)/D1(704×576/704×480)/2CIF(704×288/704×240)/CIF(352×288/352×240)/ QCIF(176×144/176×120)	
Record Rate	Main Stream:	960H/D1/HD1/2CIF/CIF (1~25/30fps)
	Extra Stream	CIF/QCIF(1~25/30ps)
Bit Rate	48~3072Kb/s	
Record Mode	Manual, Schedule(Regular(Continuous), MD), Stop	
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec	
<b>Video Detection</b>		
Trigger Events	Recording, Tour, Video Push, Email, FTP, Buzzer & Screen tips	
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank	
<b>Playback &amp; Backup</b>		
Sync Playback	1/4	
Search Mode	Time/Date, MD & Exact search (accurate to second)	
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom	
Backup Mode	USB Device / Network	
<b>Network</b>		
Ethernet	RJ-45 port (10/100M)	
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter	
Max. User Access	128 users	
Smart Phone	iPhone, iPad, Android, Windows Phone	
<b>Storage</b>		
Internal HDD	1 SATA port, up to 4TB	
<b>Auxiliary Interface</b>		
USB Interface	2 ports (2 Rear), USB2.0	

# DH-DVR2104C-H

General	
Power Supply	DC12V/2A
Power Consumption	10W(without HDD)
Working Environment	-10 ~ +55°C / 10~90%RH / 86~106kpa
Dimension(W×D×H)	205mm×205mm
Weight	0.5KG(without HDD)

## System Connection



Takes DVR2104C-H as an example

---

### Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: [overseas@dahuatech.com](mailto:overseas@dahuatech.com)

[www.dahuatech.com](http://www.dahuatech.com)

\*Design and specifications are subject to change without notice.

© 2013 Dahua Technology Co., Ltd.