

DH-HCVR5104/5108HC

4/8 All Channel 720P Mini 1U HDCVI DVR



Features

- > Up to 4/8 cameras with 1080p realtime preview
- > H.264 dual-stream video compression
- > HCVR5104/5108HC: All channel 720P
- > HDMI / VGA simultaneous video output
- > 4 channel synchronous realtime playback, GRID interface & smart search
- > 3D intelligent positioning with Dahua PTZ dome camera
- > Support 1 SATA HDD up to 4TB, 2 USB2.0
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

DH-HCVR5104/5108HC


Technical Specifications

Model		DH-HCVR5104HC	DH-HCVR5108HC
System			
Main Processor		Embedded processor	
Operating System		Embedded LINUX	
Video			
Input		4 channel, BNC	8 channel, BNC
Standard		NTSC(525Line, 60f/s), PAL(625Line, 50f/s)	
Display			
Interface		1 HDMI, 1 VGA,	
Resolution		1920×1080, 1280×1024, 1280×720, 1024×768, 800×600	
Display Split		1/4	1/4/8
Privacy Masking		4 rectangular zones (each camera)	
OSD		Camera title, Time, Video loss, Camera lock, Motion detection, Recording	
Recording			
Video/Audio Compression		H.264 / G.711	
Resolution		720P(1280×720/1280×600)/960H(960×576/960×480)/D1/4CIF(704×576 /704×480) / CIF(352×288/352×240) / QCIF(176×144/176×120)	
Record Rate	Main Stream:	720P/960H/D1/HD1/2CIF/CIF(1~25/30fps)	
	Extra Stream	CIF/QCIF(1~25/30fps)	
Bit Rate		48~6144Kb/s	
Record Mode		Manual, Schedule(Regular(Continuous), MD), Stop	
Record Interval		1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec	
Video Detection			
Trigger Events		Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips	
Video Detection		Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank	
Playback & Backup			
Sync Playback		1/4	1/4/8
Search Mode		Time/Date, MD & Exact search (accurate to second)	
Playback Functions		Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom	
Backup Mode		USB Device / Network	
Network			
Ethernet		RJ-45 port (10/100M)	
Network Functions		HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter	
Max. User Access		128 users	
Smart Phone		iPhone, iPad, Android, Windows Phone	

DH-HCVR5104/5108HC

Storage	
Internal HDD	1 SATA port, up to 4TB
Auxiliary Interface	
USB Interface	2 ports(2 Rear), USB2.0
General	
Power Supply	DC12V/2A
Power Consumption	10W(without HDD)
Working Environment	-10 ~ +55°C / 10~90%RH / 86~106kpa
Dimension(W×D×H)	Mini 1U, 325mm×245mm×45mm
Weight	1.5KG(without HDD)

System Connection



Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2013 Dahua Technology Co., Ltd.