

DH-HCVR7104/7108/7116HE-S3

4/8/16CH Tribrid 1080P Mini 1U HDCVI DVR



Features

- > Support HDCVI/Analog/IP Video input
- > H.264+/H.264 dual-stream video compression
- > HCVR7104/7108/7116HE-S3: All channel 1080P realtime recording
- > HDMI/VGA simultaneous video output
- > 4/8/16 channel synchronous realtime playback, GRID interface & smart search
- > Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek and etc.
- > ONVIF Version 2.4.1 conformance
- > 3D intelligent positioning with Dahua PTZ dome camera
- > Support 1 SATA HDD up to 6TB, 2 USB2.0 (8/16CH 1 USB3.0)
- > Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)
- > Advanced intelligent functions: Tripwire, Intrusion, Abandoned/Missing, Face Detection

DH-HCVR7104/7108/7116HE-S3


Technical Specifications

| Model | DH-HCVR7104HE-S3 | DH-HCVR7108HE-S3 | DH-HCVR7116HE-S3 |
|-------------------------------------|--|---|------------------|
| System | | | |
| Main Processor | Embedded processor | | |
| Operating System | Embedded LINUX | | |
| Video | | | |
| Input | 4 channel, BNC | 8 channel, BNC | 16 channel, BNC |
| Standard | Analog | NTSC/PAL | |
| | HDCVI | 1080P/720P HDCVI Camera | |
| | IP | 4+2 up to 5Mp | 8+4 up to 5Mp |
| Audio | | | |
| Input | 4 channel, RCA | 8 channel, RCA | 16 channel, RCA |
| Output | 1 channel, RCA | | |
| Two-way Talk | Reuse audio input/output channel 1 | | |
| Display | | | |
| Interface | 1 HDMI, 1 VGA | | |
| Resolution | 1920×1080, 1280×1024, 1280×720, 1024×768 | | |
| Display Split | 1/4/6 | 1/4/8/9 | 1/4/8/9/16 |
| Privacy Masking | 4 rectangular zones (each camera) | | |
| OSD | Camera title, Time, Video loss, Camera lock, Motion detection, Recording | | |
| Recording | | | |
| Video/Audio Compression | H.264/G.711 | | |
| Record Rate | Main Stream: | 1080P/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) | |
| | Extra Stream | D1/CIF/QCIF(1~25/30fps) | |
| Bit Rate | 1~6144Kb/s | | |
| Record Mode | Manual, Schedule(Regular(Continuous), MD), Stop | | |
| Record Interval | 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec | | |
| Video Detection & Alarm | | | |
| Trigger Events | Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips | | |
| Video Detection | Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank | | |
| Alarm Input | 8 channel | 16 channel | 16 channel |
| Relay Output | 3 channel | | |
| Intelligent Video (Optional) | Tripwire, Intrusion, Abandoned/Missing, Face Detection | | |
| Playback & Backup | | | |
| Sync Playback | 1/4 | 1/4/9 | 1/4/9/16 |
| Search Mode | Time/Date, MD & Exact search (accurate to second) | | |
| Playback Functions | Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, | | |

DH-HCVR7104/7108/7116HE-S3

| | | | |
|----------------------------|--|---|----------------------------|
| | Digital zoom | | |
| Backup Mode | USB Device/Internal SATA burner/Network | | |
| Network | | | |
| Ethernet | RJ-45 port (10/100M) | RJ-45 port (10/100M/1000M) | RJ-45 port (10/100M/1000M) |
| Network Functions | HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P | | |
| Max. User Access | 128 users | | |
| Smart Phone | iPhone, iPad, Android, Windows Phone | | |
| Storage | | | |
| Internal HDD | 1 SATA port, up to 6TB | | |
| Auxiliary Interface | | | |
| USB Interface | 2 ports(1 Rear), USB2.0 | 2 ports (1 Rear USB3.0, 1 Front USB2.0) | |
| RS485 | 1 port, For PTZ Control | | |
| General | | | |
| Power Supply | DC12V/2A | | DC12V/3A |
| Power Consumption | 10W(without HDD) | | |
| Working Environment | -10°C ~ +55°C / 10%~90%RH / 86~106kpa | | |
| Dimension(W×D×H) | Mini 1U, 325mm×255mm×55mm | | |
| Weight | 1.5KG(without HDD) | | |

System Connection



*Takes HCVR7018HE-S3 as an example

Dahua Technology Co., Ltd.

1199' BinAn Road, Binjiang District, Hangzhou, China
 Tel: +86-571-87688883
 Fax: +86-571-87688815
 Email: overseas@dahuatech.com
 www.dahuatech.com

*Design and specifications are subject to change without notice.