External mass storage device with RAID 6 technology



The DAS-600 is a powerful external FC-SATA storage system for connection to recorders of the DMS series.

Thanks to its redundant, modular design with hot-swappable components, its innovative storage management software and a flexible interface support with highly reliable storage devices, it offers a high performance security solution with highest scalability and functionality.

Its 2HU housing can contain max. 12 SATA HDDs in lockable slide-in units. They can be configured for redundant recording with the integrated graphical user interface (web browser).

- The system is ready for operation incl. particularly suited and Dallmeier approved and authorised HDDs
- Can be equipped with up to 4 expansion housings with a total maximum number of 60 hard drives, expansion via SAS-Expander
- Standard RAID level 6 (RAID level 0, 1, 5, 10 and 50 upon request)
- Gross capacity (for 2 TB HDD): 24 TB (net: 18 TB)
- Installed RAID controller supports RAID level 0, 1, 5, 6, 10, 50
- Installed FC controller for external connection

- Up to 2x 4 GB/s FC interface
- Hot-spare functionality and automatic rebuild
- Hot-plug functionality: HDDs, power supply units and fans can be exchanged during operation
- Alarm function via PGuard on hard disk, fan and power supply unit failure
- Management and alarm via installed Ethernet interface possible
- Requirements: 1.) Software version from 6.0.9 (for hybrid recorders) / 2.) Air-conditioned dust-free environment, server environment is ideal

Variants	
Item number	
000225.407	DAS-600 12000 with 6x 2 TB HDDs (RAID 5) Net storage capacity: approx. 8 TB
000225.408	DAS-600 12000 with 6x 2 TB HDDs (RAID 6) Net storage capacity: approx. 6 TB
000225.409	DAS-600 18000 with 9x 2 TB HDDs (RAID 5) Net storage capacity: approx. 14 TB
000225.410	DAS-600 18000 with 9x 2 TB HDDs (RAID 6) Net storage capacity: approx. 12 TB
000225.411	DAS-600 24000 with 12x 2 TB HDDs (RAID 5) Net storage capacity: approx. 20 TB
000225.412	DAS-600 24000 with 12x 2 TB HDDs (RAID 6) Net storage capacity: approx. 18 TB

Options	
Item number	
001330	FC cable for DAS storage expansion
001348	HDD incl. removable tray, 1000 GB (DAS-303 / 600)
001349	HDD incl. removable tray, 2000 GB (DAS-600)

Compatible hosts DMS 80/160/240/240 HSR/240 IPS

PVS IV Plus SeMSy® S-PC Plus

SeMSy® Pro II Backup Server Plus

Specifications

Max. Number of hosts Max. 2x Gross storage capacity Up to 24 TB Type of the HDD units 3,5" SATA Max. nr. of HDD units Max. 12x Storage capacity per HDD unit Up to 2 TB Max. 4x DAS-600 E Extension

Integrated functions

StorView Standard Management Software StorView Global (optional) Compatible operating systems LINUX, Windows 2000/ XP/ 2003/7

RAID controller Max. 2x RAID Levels 0/ 1/ 5/ 6/ 10/ 50 RAID Controller Hot-plug Power supply Hot-plug Yes (redundant) HDDs Hot-plug

Ventilator Hot-plug **Further specifications**

Interfaces 1x RJ45, 10/100/1000 Mbps

1 x 3Gb/s SAS out 2 x 4Gb/s Fibre Channel

Yes (redundant)

Applicability In a 19" rack

Voltage supply 100/240V AC +/-10% (50/60 Hz), max. 5A

Yes (RAID Cache) Power consumption Max. 250 W

Max. 1211 BTU/h (with 12x HDDs) Heat power 5 ° - 40 °C (41° - 104 °F) Operating temperature Humidity 10 - 80% RH non condensing Dimensions (W x H x D) Approx. 444 x 88 (2HU) x 550 mm

Weight Approx. 18 kg (incl. 12x HDDs)

CCC, BSMI, CE, UL, cUL, RoHS (R5), Microsoft WHQL, Approvals/certifications Microsoft RAID System Submission - w/MPIO (Single Host)