

## DIS-1/S



### 1-channel MPEG-2 video streaming server

- The DIS-1/S streaming server is a 1-channel audio and video recorder for analogue cameras. At the same time as recording, the audio and video data can be transmitted in real-time as a stream via a network (RTP protocol).

The DIS-1/S is configured with a graphical user interface. It allows the configuration of all recording and streaming settings. Four input and four output contacts are available for control and switching tasks. Playback, evaluation and archiving of the recorded data are also done via the network using a PC / PView or the management system SeMSy®.

#### Features:


- Analogue video inputs CVBS / S-Video
- Video compression MPEG-2
- Audio compression MPEG-1
- Bit rate (constant or dynamic) up to 16 Mbit/Sec.
- Image rate up to 25 frames/sec.
- Resolution up to 720 x 576 (PAL) / 720 x 480 (NTSC)
- Memory capacity up to 500 GB with 2 HDDs
- Configuration with browser in the LAN
- Simultaneous and real-time recording and streaming
- Evaluation with SeMSy® or PView in the LAN

#### Options:

- Max. 2 hard disks à 500 GB
- Parallel recording

#### Item number

- 001.041.0



## DIS-1/S

### Format

Video standard	PAL / NTSC
Video compression	MPEG-2 MP@ML
Audio compression	MPEG-1 Layer 2

### Video IN / OUT

Video IN (CVBS)	1 x BNC
Video IN (S-Video)	1 x mini DIN 4
Video OUT (FBAS)	1 x BNC
Video OUT (S-Video)	1 x mini DIN 4

### Audio IN / OUT

Audio IN	2 x RCA jack, stereo
Audio OUT	2 x RCA jack, stereo

### Recording

Recording speed PAL/NTSC	25 / 30 fps
Video bit rate	0.25 - 16 MBit/Sec
	Constant and variable
Audio bit rate	192 - 384 kBit
Resolution PAL / NTSC	720 x 576 / 720 x 480

### Hard disks

Quantity	Max. 2
Type	3.5"
Interface	ATA / ATAPI

### Interfaces

Control inputs	4 x on 6-pole Weidmüller connection strip
Serial	1 x 9-pol D-SUB, RS 232
IR remote operation	Multi protocol compatible
USB	2 x Typ A, USB 1.1
LAN	1 x RJ45, 10/100 Mbit

### Other hardware details

Mains voltage (incl. admissible tolerance)	100V AC – 240V AC, 50/60 Hz
Power consumption	Appr. 28 W
Dimensions	W 425 x H 43 x D 350 mm
Temperature	0 - 50° C
Humidity	5 - 95 %
Weight	Max. 8 kg
Languages	German, English, French, Spanish (others on request)
Approvals/certifications	CE, C-TICK, FCC, UL, CB, VCCI 2002
Warranty	36 months