



The VNS 1 is a 1 channel audio and video streamer with recording capability. It is able to receive, via an Ethernet network, audio and video streams in different encodings, record and playback them and output them in real time as a stream.

The VNS 1 is a stand-alone streamer. The compact and robust design of the streamer allows for a flexible use of the device, regardless of the location. The VNS 1 is furthermore designed for the installation and operation in a 19" module rack.

- 1x IP based video channel
- Simultaneous real-time recording, streaming and playback
- Supported video formats: MPEG-2/-4 H.264
- Supported audio formats: MPEG-1 Layer 2, G.722 1)
- Bit rate up to 16 Mbps and frame rate up to 25 fps
- Resolutions: SD, HD, (720p, 10870i, 1080p)

- Evaluation with SeMSy® or PView via Ethernet
- Integrated motion detection
- Configuration and firmware update through web browser via Ethernet
- Linux operating system on Flash memory
- Integrated hard disk
- DIN EN 50130-4 compliant

Variants

008.007.012.101

VNS 1 with 1x 120 GB HDD 1x IP based video channel

Please note: this product is only available on request!

Options

002.001.390 19" module rack, (L390 mm x 3HU) for the installation of up to 10 single devices, incl. power supply unit and its depositing rack

000.214 19" bracket, for up to 4 units (1HU)

Item number

Item number

© 2009 Dallmeier electronic

07-07-2009

Product specifications subject to change without notice.

Technical specifications

Features Recording, streaming, play-back

Max. camera inputs 1.

Video compression MPEG-2/MPEG-4, MJPEG

Audio compression MPEG-1 Layer2

Resolution D1, 4CIF, Half D1, 2CIF, CIF, QCIF

Frame rate at all resolution 6.25 / 12.5 / 25 fps
Bit rate -video- 0.25 - 16 Mbps
Bit rate -audio- 64 - 384 Kbps

Interfaces

Video IN Streaming via Ethernet
Video OUT Streaming via Ethernet
Audio IN Streaming via Ethernet
Audio OUT Streaming via Ethernet
Ethernet 1x RJ45, 10/100 Mbit/s

Ethernet protocols Unicast: IPv4, TCP, HTTP, IGMP, DHCP, ARP, NTP, UDP

Multicast: UDP, RTP, RTCP

Contact IN 4x Contact OUT 4x

Integrated functions

SmartFinder Integrated
Recording mode Permanent, contact

Further specifications

Internal HDDs -standard-1x 2.5" Internal storage capacity 120 GB Via web browser PAL / NTSC Configuration Video norm Power consumption Max. 17 W Voltage supply 12 V DC Max. 58 BTU/h Heating power Dimensions W x H x D 110 x 44 x 245 mm Weight Approx. 1.5 Kg

Ambient temperature 5° - 40° C
Humidity -not condensingOperating system Linux

Languages German, English, French, Italian (others on request)