

Instruction

Smart gateway is the control center of smart home. It supports standard Zigbee 3.0 protocol. This allows it to seamlessly connect with various wireless accessories through the Dnake Smart Life App including smoke sensors, temperature and humidity sensors, door and window sensors, motion sensors, water leak sensors, gas sensors and smart button etc. The versatility of the Smart Gateway enables users to create a comprehensive and interconnected smart home ecosystem.

Smart Gateway



Key Features

- Adopts standard ZigBee 3.0 protocol and Ethernet protocol, good compatibility
- Support up to 50 Zigbee sub-devices
- Support customized scenes, customized smart linkage
- Fashion and simple design

Technical Parameters

- Model Name: HS6GW-TY
- Working Voltage: DC5V 1A (adapter power supply)
- Wireless Connection: Standard Zigbee 3.0
- Connecting to Internet: RJ45 Ethernet
- Zigbee Communication distance: $\leq 70\text{m}$ (Open area)
- Adapter: 100V~240VAC, 5V/1A DC
- Working temperature: -10°C to 55°C
- Working humidity: Maximum 95%RH (Non-condensing)
- Status indicator: 2LED (Status/Lan)
- Operation hole: 1 hole (reset)
- Dimension: 89x89x23.5mm
- Packing List: Gateway+Adapter+Network cable+USB Cable+User manual+Accessories

