

DIR-4108H/1.2TV

Home | Security | Recording | Recorders

DIR-4108H/1.2TV
Digital Video Recorder (8 Channels), H.264, MPEG4,
1.25TB, 100fps, Ethernet

Art-Nr. 72831



Main Features

Quadplex Operation	Secondary Storage / Archiving via USB 2.0
H.264 and MPEG-4 Video Compression	1000Gbyte SATA HDD's (no HDD extension possible)
Recording Speed: 100 ips max.	Live Picture & Playback Zoom (2x)
8 BNC Inputs / VGA, Composite Output	Covert Camera Recording
Network Connectivity (10/100Base-T Ethernet)	Integrated Motion Detector
8 Alarm Inputs / 1 Output	IR Remote Control and Mouse Control

Specifications

Series	eneo DIR
Operation mode	Quadplex
Video standard	PAL/NTSC (automatic selection)
Video inputs (amount)	8
Video inputs	1Vp-p, (C)VBS, 75ohms, BNC
Main exits	CVBS, VGA
Video outputs	1Vp-p, (C)VBS, 75ohms, BNC
Spot monitor	-
IP channels	-
Audio inputs	-
Alarm inputs	8, selectable between NO and NC
Activity detection	16x12 grid, Sensitivity levels: 5, Discrimination size: 192 levels. Minimum size for detection: 15 levels

DIR-4108H/1.2TV

(Continuation Spezifications)

Covert Camera Recording	Available
Alarm outputs	NO/NC contact
Alarm notification	E-mail
Alarm reset input	TTL input
Event Logs	No limit for motion, video loss
System logs	up to 5000, user login/out, config. changes, remote access, connects/disconnects and errors, disk read and write errors
Max. recording resolution	672 x 544
Resolution	720x576 Pixels (PAL/Display)
Compression standard	MPEG4, H.264, (H.264: advanced compression engine provides smaller data size without significant picture quality distortion)
Image size	Low: 2/2.4kB, Standard: 4/4.8kB, High: 8/9.6kB, Very high: 12/14.4kB (NTSC/PAL).
Max. recording rate	100 B./Sek.
Recording speed	100 ips at 336x272 Px. / PAL, 50 ips at 672x272 Px. / PAL, 25 ips at 672x544 Px. / PAL
Digital storage media	SATA hard disk
Harddisk capacity (internal)	1250 GB
Max. harddisk capacity (internal)	2000 GB
Pre-alarm recording	up to 60sec.
Post-alarm recording	up to 60sec.
Playback	1, 4, 8 channel Split, PIP
Playback speed	100 images/sec. at CIF (336x272 Px. / PAL) and duplex
Zoom function	2x
Intergrated writer	no
Archiving	USB (HDD's, CD-RW, Flash drive)
Secondary Storage	via USB 2.0. Network Data Export: Clip Player, AVI, JPG, BMP
Control units (external)	Mouse, Remote Control
Remote control	Wireless remote control enabled
Remote access	Remote Software, Browser
Remote Software	For remote administration and search function (RASplus, Webguard, supplied with the unit)
Time synchronization	Via Network time protocol. Operation as Network time server
Search function	Date/Time, Record table, Calendar, Event, Motion, Museum
Menu languages	German, English, Italian, French, Spanish, Polish, Russian, Czech, Hungarian
Ethernet interface	10Base-T/100-Base-TX, RJ-45
Network protocols	TCP/IP, ADSL, DHCP, DVRNS
Transmission rate (Network)	50 ips (CIF), 25 ips (2CIF), PAL
Remote configuration	via web browser
Interfaces external storage	USB, 2x USB 2.0

DIR-4108H/1.2TV

(Continuation Specifications)

Serial interfaces	RS-232, RS-485, RS-485 for telemetry control (proved protocols: eneo Fastrax, Pelco P&D)
Text insertion interface	RS-232
Security	User groups access rights programmable for each group
Supply voltage	100VAC~230VAC, 50/60Hz
Power consumption	approx. 80watts
Temperature range (Operation)	+5°C ~+40°C
Housing	Steel metal with plastic front, desktop design
Colour	Antracite
Dimensions (HxWxD)	88x430x405mm
Weight	5.3kg
Parts supplied	Mouse, IR Remote control, Power supply unit, 19" rack mount kit, Remote Viewer Software, Manual
Certificates	CE

Optional accessories

74149	KBD-2	System Keyboard with 3-Axis Joystick and Jog Shuttle, 12VDC
74092	EDC-KBDM-3	System Keyboard w. Joystick, 5" Monitor 12VDC, Fastrax Protocol
74088	EDC-KBD1	System Keyboard with 3-axis Joystick, 12VDC
74746	KBD-NSC-100	Network System Controller with 3-Axis Joystick and Jog Shuttle, 5VDC
72934	USB-8COM	Serial Text Interface Converter 8x RS232 for DLR-3/4, DTR and DPR

