

EHL-W/ECLKB

Home | Security | Housings | for Boxed Cameras

EHL-W/ECLKB

Weatherproof Housing (300mm) w. Heater,

Thermostat, Wall Bracket, RAL9002, 12/24V

Art-Nr. 79654



Main Features

Camera weather protection w. integrated sunshield
Fold-down aluminium housing body
UV resistant ABS plastic front and back part
3mm glass front window
Accepts camera & lens combinations up to 252mm
Insulated camera mounting

2 cable entry glands M16x1.5mm
12-24V window heater included
Protection rating: IP66
Housing colour: RAL9002
Wall bracket with swivel head included
Option: Blower kit, Camera support kit

Specifications

Series	eneo EHL
Maximum installation length	252
Max. camera size (LxWxH)	252x85x75mm
Space for power supply	50mm
Cable entries	2x M16x1.5mm (for cable diam. 4.5~10mm)
Clear Shield	no
Window heater	yes, 12~24V/20watts (PTC)
Thermostat	On: +15°C, Off: +22°C
Blower	optional
Wiper	no
Supply voltage	12~24V
Sunshield	yes
Hidden cable management	no

EHL-W/ECLKB

(Continuation Spezifications)

Integrated wall mount	no
Protection rating	IP66
Housing	outdoor
Housing material	aluminium
Housing	aluminium with plastic covers (ABS)
Colour (housing)	RAL9002
Temperature range	-20°C ~+50°C
Weight	2.4kg (incl. wall bracket)
Parts supplied	Camera housing, Wallbracket, Manual

Optional accessories

79665	EHL-BLS/12VDC	Blower Kit 230V/50Hz with Thermostat for EHL-W/ECLKB Housing, 12VDC
79593	PM-6D	Pole Mount Adapter for 2 Wall Mounts, (50-140mm Pole), RAL9002
79604	SU-6	Camera Height Adjustment Kit for VHK and EHL Housings (3 Diff. Slides and Screws)
79592	PM-6S	Pole Mount Adapter for 1 Wall Mount, (50-140mm Pole), RAL9002
70457	AK-3	Camera Connection box, 230VAC Input, 24VAC-3.2A, 12VDC-1A Outputs

EHL-W/ECLKB

Home | Security | Housings | for Boxed Cameras

Technical drawing

