



EKR-PTZFI-R1

Article-No.: 75209

RS-232/RS-485 Telemetry Preset
Receiver 230VAC, for P/T Heads
24V/230VAC

Main features

Zoom lens and 230/24VAC P/T head control
Receiver for RS-485 control
Supply voltage: 230VAC

Preset positioning
Auxiliary switch outputs
Weatherprotected box

Specifications

Presets	40
Cable entry	6x cable glands PG11
Camera voltage supply	12VDC max.350mA, or 24VAC max.180mA
Lens control voltage	3-12VDC adjustable (max. 100mA)
P/T head control voltage	230VAC or 24VAC selectable
Error output	2 Dry contacts: 1A 230VAC, 1A 24VAC (AUX3, AUX4)
Trigger input	Serial input selectable: RS232 or RS485 integrated protocol Pelco D or optional data transmission on coax cable with EKR -PTZFI-CB (EDP 75211)
Control functions	Left/Right/Up/Down, Zoom/Focus/Iris, Aux.
Temperature range	0°C to +50°C
Supply voltage	230VAC, 50/60Hz
Power consumption	100W max.
Protection rating	IP56
Housing	plastic
Colour	light grey
Dimensions (HxWxD)	128x237x337mm
Weight	3,6kg

Optional Accessories

Image	Artikel-Nr. / Typ	Description
	EKR-PTZFI-CB	Coax Telemetry Board for EKR-PTZFI-R1 Receiver

Your partner for eneo products:

